

Chapter 12

APPENDIX - MSDS

12.1 MSDS M0090 Fiberfrax® QF Cements.....	12-2
12.2 MSDS M0042 Fiberfrax® Duraboard®	12-8
12.3 Fiberfrax® Refractory Ceramic Fiber MSDS 0001	12-14
12.4 MSDS M0055 Fiberfrax® High Purity Papers	12-20
12.5 Kaowool® Insulation MSDS 203	12-26
12.6 MSDS 0732 RTV Silicone 732	12-31
12.1 MSDS MagnaForm Boards	12-32

12.1 MSDS M0090 Fiberfrax® QF Cements

maximize rodent respirability.



MATERIAL SAFETY DATA SHEET

MSDS No. M0090

Effective Date: 03/09/2004

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Group: REFRactory CERAMIC FIBER PRODUCT
Chemical Name: VITREOUS ALUMINOSILICATE FIBER
Synonym(s): RCF, ceramic fiber, synthetic vitreous fiber (SVF), man-made vitreous fiber (MMVF), man-made mineral fiber (MMMF)

FIBERFRAX® QF CEMENTS
QF-150 Cement, QF-180 Cement, QF-180-AB Cement, QF-180 Blue Cement

Manufacturer/Supplier: Unifrax Corporation
 2351 Whirlpool St.
 Niagara Falls, NY 14305-2413

Product Stewardship Information Hotline
 1-800-322-2293 (Monday - Friday 8:00 a.m. - 4:30 p.m. EST)
 For additional MSDSs, visit our web page, <http://www.unifrax.com>,
 or call Unifrax Customer Service at (716) 278-3872

CHEMTREC Assist: CHEMTREC will provide assistance for chemical emergencies. Call 1 - 800-424-9300

2. COMPOSITION / INFORMATION ON INGREDIENTS

COMPONENTS	CAS NUMBER	% BY WEIGHT
Refractories, Fibers, Aluminosilicate	142844-00-6	40-60
Water	7732-18-5	20-50
Silica (amorphous)	7631-86-9	10-15
Hydrated magnesium aluminum silicate mineral	12199-37-0	1-3
(See Section 8 "Exposure Controls / Personal Protection" for exposure guidelines)		

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

CAUTION! MAY BE HARMFUL IF SWALLOWED.
MAY CAUSE SKIN AND EYE IRRITATION.
DRIED, ABRASIVE PRODUCT MAY CAUSE RESPIRATORY TRACT IRRITATION AND POSE POSSIBLE CANCER HAZARD BY INHALATION.
 (See Section 11 for more information)

CHRONIC EFFECT

There has been no increased incidence of respiratory disease in studies examining occupationally exposed workers. In animal studies, long-term laboratory exposure to doses hundreds of times higher than normal occupational exposures has produced fibrosis, lung cancer, and mesothelioma in rats or hamsters. The fibers used in those studies were specially sized to

TARGET ORGANS:		OTHER POTENTIAL EFFECTS
Respiratory Tract (nose & throat), Eyes, Skin		
RESPIRATORY TRACT (nose & throat) IRRITATION:		If dried, airborne product is inhaled in sufficient quantity, may cause temporary, mild mechanical irritation to respiratory tract. Symptoms may include scratchiness of the nose or throat, cough or chest discomfort.
EYE IRRITATION:		May cause temporary, mild mechanical irritation. Fibers may be abrasive; prolonged contact may cause damage to the outer surface of the eye.
SKIN IRRITATION:		Exposure to dried product may cause temporary, mild mechanical irritation. Exposure may also result in inflammation, rash or itching.
GASTROINTESTINAL IRRITATION:		Unlikely route of exposure. Small amounts swallowed incidental to normal handling operations are not likely to cause injury.
MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:		Pre-existing medical conditions, including dermatitis, asthma or chronic lung disease may be aggravated by exposure; individuals who have a history of allergies may experience greater amounts of skin and respiratory irritation.
HAZARD CLASSIFICATION		
Although studies, involving occupationally exposed workers, have not identified any increased incidence of respiratory disease, results from animal testing have been used as the basis for hazard classification. In each of the following cases, the conclusions are qualitative only and do not rest upon any quantitative analysis suggesting that the hazard actually may occur at current occupational exposure levels.		
In October 2001, the International Agency for Research on Cancer (IARC) confirmed that RCF Group 2b (possible human carcinogen) remains the appropriate IARC classification for RCF.		
The Seventh Annual Report on Carcinogens (1994), prepared by the National Toxicology Program (NTP), classified respirable RCF and glasswool as substances reasonably anticipated to be carcinogens.		
The American Conference of Governmental Industrial Hygienists (ACGIH) has classified RCF as "A2-Suspected Human Carcinogen."		
The Commission of The European Communities (DG XI) has classified RCF as a substance that should be regarded as if it is carcinogenic to man.		
The State of California, pursuant to Proposition 65, The Safe Drinking Water and Toxic Enforcement Act of 1986, has listed "ceramic fibers (airborne fibers of respirable size)" as a		

Appendix - MSDS

chemical known to the State of California to cause cancer.

The Canadian Environmental Protection Agency (CEPA) has classified RCF as "probably carcinogenic" (Group 2).

The Canadian Workplace Hazardous Materials Information System (WHMIS) – RCF is classified as Class D2A – Materials Causing Other Toxic Effects

Hazardous Materials Identification System (HMIS) –
Health 1* Flammability 0 Reactivity 0 Personal Protection Index: X (Employer Determined)
(* denotes potential for chronic effects)

4. FIRST AID MEASURES

FIRST AID PROCEDURES

RESPIRATORY TRACT (nose & throat) IRRITATION:

If respiratory tract irritation develops, move the person to a dust free location. Get medical attention if the irritation continues. See Section 8 for additional measures to reduce or eliminate exposure.

EYE IRRITATION:

If eyes become irritated, flush immediately with large amounts of lukewarm water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Do not rub eyes. Get medical attention if irritation persists.

SKIN IRRITATION:

If skin becomes irritated, remove soiled clothing. Do not rub or scratch exposed skin. Wash area of contact thoroughly with soap and water. Using a skin cream or lotion after washing may be helpful.

GASTROINTESTINAL IRRITATION:

If gastrointestinal tract irritation develops, move the person to a dust free environment.

NOTES TO PHYSICIANS:

Skin and respiratory effects are the result of temporary, mild mechanical irritation, fiber exposure does not result in allergic manifestations.

5. FIRE FIGHTING MEASURES

NFPA Codes: Flammability: 0 Health: 1 Reactivity: 0 Special: 0

NFPA Unusual Hazards: None
Flammable Properties: None
Flash Point: None
Hazardous Decomposition Products:
Thermal decomposition of binder from fires or from first heat of product may release smoke, carbon monoxide and carbon dioxide. Use adequate ventilation or other precautions to eliminate exposure to vapors resulting from thermal decomposition of

binder. Exposure to thermal decomposition fumes may cause respiratory tract irritation, bronchial hyper-reactivity or an asthmatic-type response.

Unusual Fire and Explosion Hazard: None
Extinguishing Media: Use extinguishing media suitable for type of surrounding fire.

6. ACCIDENTAL RELEASE MEASURES

SPILL PROCEDURES

Avoid creating airborne dust. Dust suppressing cleaning methods such as wet sweeping or vacuuming should be used to clean the work area. If vacuuming, the vacuum must be equipped with a HEPA filter. Compressed air or dry sweeping should not be used for cleaning.

7. HANDLING AND STORAGE

Normal conditions of use and application are not expected to release respirable particulates of airborne fibers. Removal of used product, sanding, scraping, or otherwise destroying the integrity of the dried product may result in the release of particulates and fibers. During such operations where fibers could possibly be released, appropriate respiratory protection should be provided as discussed below and/or in Section 8 under Respiratory Protection.

STORAGE

Store in original container in a dry area. Keep container closed when not in use.

HANDLING

Handle ceramic fiber carefully. Limit use of power tools unless in conjunction with local exhaust. Use hand tools whenever possible. Frequently clean the work area with HEPA filtered vacuum or wet sweeping to minimize the accumulation of debris. Do not use compressed air for clean-up.

EMPTY CONTAINERS

Product packaging may contain residue. Do not reuse.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE GUIDELINES – RCF

COMPONENTS	OSHA PEL	MANUFACTURER REG
Refractories, Fibers, Aluminosilicate	None Established*	0.5 f/cc, 8-hr. TWA**

* There is no specific regulatory standard for RCF in the U.S. OSHA's "Particulate Not Otherwise Regulated (PNOR)" standard [29 CFR 1910.1000, Subpart Z, Air Contaminants] applies generally. Total Dust 15 mg/m³. Respirable Fraction 5 mg/m³.

** The Refractory Ceramic Fibers Coalition (RCFC) has sponsored comprehensive toxicology and epidemiology studies to identify potential RCF-related health effects [see Section 11 for more details], consulted experts familiar with fiber and particle science, conducted a thorough review of the RCF-related scientific literature, and further evaluated the data in a state-of-the-art

Chapter 12

MANUFACTURER'S RESPIRATORY PROTECTION RECOMMENDATIONS WHEN HANDLING RCF PRODUCTS	
Respirable Airborne Fiber Concentration (levels are 8-hr time-weighted averages)	Respirator Recommendation [†]
Not yet determined but expected to be below 5.0 f/cc based on operation	Half-face, air purifying respirator equipped with a NIOSH certified P100 particulate filter cartridge
"Reliably" less than 0.5 f/cc	Optional
0.5 f/cc to 5.0 f/cc	Half-face, air purifying respirator equipped with a NIOSH certified P100 particulate filter cartridge
5.0 f/cc to 25 f/cc	Full-facepiece, air purifying respirator equipped with a NIOSH certified P100 particulate filter cartridge or PAPR
Greater than 25 f/cc	PAPR with tight-fitting full facepiece or a supplied air respirator in continuous flow mode

OTHER OCCUPATIONAL EXPOSURE LEVELS (OEL)
RCF-related occupational exposure limits vary internationally. Regulatory OEL examples include: Australia – 0.5 f/cc; Austria – 0.5 to 1.0 f/cc; Canada – 0.5 to 1.0 f/cc; Denmark – 1.0 f/cc; France – 0.6 f/cc; Germany – 0.5 f/cc; Netherlands – 1.0 f/cc; New Zealand – 1.0 f/cc; Norway – 2.0 f/cc; Poland – 2.0 f/cc; Sweden – 1.0 f/cc; United Kingdom – 2.0 f/cc. Non-regulatory OEL examples include: ACGIH TLV 0.2 f/cc; RCFC REG 0.5 f/cc. The objectives and criteria underlying each of these OEL decisions also vary. The evaluation of occupational exposure limits and determining their relative applicability to the workplace is best performed, on a case-by-case basis, by a qualified Industrial Hygienist.

EXPOSURE GUIDELINES – OTHER INGREDIENTS

COMPONENTS	OSHA PEL	MANUFACTURER REG
Wafer	None established	None established
Silica (amorphous) Hydrated magnesium aluminum silicate mineral	20 mg/m ³ or 80 mg/m ³ / % SiO ₂ 5 mg/m ³ PEL (resp. fraction), 15 mg/m ³ PEL (total dust) as PNCR	None established None established None established

OTHER OCCUPATIONAL EXPOSURE LEVELS (OEL)

Non-regulatory OEL examples include: ACGIH TLVs (TWA); Wafer – None established, Silica (amorphous) – 10 mg/m³. Hydrated magnesium aluminum silicate mineral, as PNOC – 10 mg/m³ (total dust), 3 mg/m³ (respirable fraction)

ENGINEERING CONTROLS

Use engineering controls such as local exhaust ventilation, point of generation dust collection, down draft work stations, emission controlling tool designs, and materials handling equipment designed to minimize airborne fiber emissions.

PERSONAL PROTECTION EQUIPMENT

Respiratory Protection – RCF:

When engineering and/or administrative controls are insufficient to maintain workplace concentrations within the 0.5 f/cc REG, the use of appropriate respiratory protection, pursuant to the requirements of OSHA Standards 29 CFR 1910.134 and 29 CFR 1926.103, is recommended. The following information is provided as an example of appropriate respiratory protection for aluminumsilicate fibers. The evaluation of workplace hazards and the identification of appropriate respiratory protection is best performed, on a case by case basis, by a qualified Industrial Hygienist.

Skin Protection:

Wear gloves, head coverings and full body clothing as necessary to prevent skin irritation. Washable or disposable clothing may be used. If possible, do not take unwashed clothing home. If soiled work clothing must be taken home, employers should ensure employees are thoroughly trained on the best practices to minimize or avoid non-work dust exposure (e.g., vacuum clothes before leaving the work area, wash work clothing separately, rinse washer before washing other

Appendix - MSDS

household clothes, etc.).

Eye Protection:

Wear safety glasses with side shields or other forms of eye protection in compliance with appropriate OSHA standards to prevent eye irritation. The use of contact lenses is not recommended, unless used in conjunction with appropriate eye protection. Do not touch eyes with soiled body parts or materials. If possible, have eye-washing facilities readily available where eye irritation can occur.

HEALTH DATA SUMMARY

Epidemiological studies of RCF production workers have indicated no increased incidence of respiratory disease nor other significant health effects. In animal studies, long-term, high-dose inhalation exposure resulted in the development of respiratory disease in rats and hamsters.

EPIDEMIOLOGY

The University of Cincinnati is conducting an ongoing epidemiologic investigation. The evidence obtained from employees in U. S. RCF manufacturing facilities is as follows:

9. PHYSICAL AND CHEMICAL PROPERTIES

ODOR AND APPEARANCE	White, odorless, fibrous material
CHEMICAL FAMILY:	Vitreous Aluminosilicate Fibers
BOILING POINT:	Not Applicable
WATER SOLUBILITY (%):	Not Soluble in Water
MELTING POINT:	1760° C (3200° F)
SPECIFIC GRAVITY:	QF-150 Cement - 1.681 - 1.833 QF-180 Cement - 1.648 - 1.708 QF-180 AB & QF-180 Blue Cement - 1.456 - 1.520
VAPOR PRESSURE	Not Applicable
pH:	Not Applicable
VAPOR DENSITY (Air = 1):	Not Applicable
% VOLATILE	Not Applicable
MOLECULAR FORMULA:	Not Applicable

10. STABILITY AND REACTIVITY

CHEMICAL STABILITY:
INCOMPATIBILITY:
Stable under conditions of normal use.
Soluble in hydrofluoric acid, phosphoric acid, and concentrated alkali.

CONDITIONS TO AVOID:

HAZARDOUS DECOMPOSITION PRODUCTS:

Thermal decomposition of binder from fires or from fast heat of product may release smoke, carbon monoxide and carbon dioxide. Use adequate ventilation or other precautions to eliminate exposure to vapors resulting from thermal decomposition of binder. Exposure to thermal decomposition fumes may cause respiratory tract irritation, bronchial hyper-reactivity or an asthmatic-type response.

HAZARDOUS POLYMERIZATION:

None.

Not Applicable.

11. TOXICOLOGICAL INFORMATION

Normal conditions of use and application are not expected to release respirable particulates of airborne fibers. Removal of used product, sanding, scraping, or otherwise destroying the integrity of the dried product may result in the release of particulates and fibers. The toxicological information below applies to the aluminosilicate fiber portion of the dried product.

A number of toxicological studies designed to identify any potential health effects from RCF exposure have been completed. In one study, conducted by the Research and Consulting Company (Geneva, Switzerland), rats and hamsters were exposed to 30 mg/m³ (about 200 fibers/cc) of specifically-prepared RCF for 6 hours/day, 5 days/week, for up to 24 months. In rats, a statistically significant increase in lung tumors was observed; two mesotheliomas (cancer of the pleural lining between the chest wall and lung) were also identified. Hamsters did not develop lung tumors; however, interstitial fibrosis and mesothelioma was found. Some, in the scientific community, have concluded that the "maximum tolerated dose" was exceeded and that significant particle contamination was a confounding issue; therefore, these study findings may not represent an accurate assessment of the potential for RCF to produce adverse health effects.

In a related multi-dose study with a similar protocol, other rats were exposed to doses of 16 mg/m³, 9 mg/m³, 3 mg/m³ which corresponds to about 115, 75, and 25 fibers per cubic centimeter respectively. This study found no statistically significant increase in lung cancer. Some cases of pleural and parenchymal fibrosis were seen in the 16 mg/m³ dose group. Some cases of mild

15. REGULATORY INFORMATION

fibrosis and one mesothelioma were observed in the 9 mg/m³ group. No acute respiratory effects were seen in the rats in the 3 mg/m³ exposure group, which suggests that there may be a dose/response threshold, below which irreversible respiratory impacts do not occur.

Other toxicological studies have been conducted which utilized non-physiological exposure methods such as intrapleural, intraperitoneal and intratracheal implantation or injection. Some of these studies have found that RCF is a potential carcinogen. Some experts, however, suggest that these tests have limited relevance because they bypass many of the biological mechanisms that prevent fiber deposition or facilitate fiber clearance.

To obtain more epidemiology or toxicology information, please call the toll free telephone number for the Unifrax Corporation Product Stewardship Program found in Section 16 - Other Information.

12. ECOLOGICAL INFORMATION

No ecological concerns have been identified.

13. DISPOSAL CONSIDERATIONS

WASTE MANAGEMENT

To prevent waste materials from becoming airborne during waste storage, transportation and disposal, a covered container or plastic bagging is recommended.

DISPOSAL

RCF, as manufactured, is not classified as a hazardous waste according to Federal regulations (40 CFR 261). Any processing, use, alteration or chemical additions to the product, as purchased, may alter the disposal requirements. Under Federal regulations, it is the waste generator's responsibility to properly characterize a waste material to determine if it is a "hazardous" waste. Check local, regional, state or provincial regulations to identify all applicable disposal requirements.

UNITED STATES REGULATIONS

EPA: Superfund Amendments and Reauthorization Act (SARA) Title III - This product does not contain any substances reportable under Sections 302, 304, 311, (40 CFR 372). Sections 311 and 312 (40 CFR 370) apply (delayed hazard).

Toxic Substances Control Act (TSCA) - All substances in this product are listed, as required, on the TSCA inventory. RCF has been assigned a CAS number; however, it is a simple mixture and therefore not required to be listed on the TSCA inventory. The components of RCF are listed on the inventory.

Comprehensive Environmental Response, Compensation and Liability Act (CERCLA) and the **Clean Air Act (CAA)** - RCF contains fibers with an average diameter greater than one micron and thus is not considered a hazardous air pollutant.

Comply with Hazard Communication Standards 29 CFR 1910.1200 and 29 CFR 1926.59 and the Respiratory Protection Standards 29 CFR 1910.134 and 29 CFR 1926.103.

California: Ceramic fibers (airborne particles of respirable size) is listed in **Proposition 65, The Safe Drinking Water and Toxic Enforcement Act of 1986** as a chemical known to the State of California to cause cancer. RCF products are not known to be regulated by states other than California; however, state and local OSHA and EPA regulations may apply to these products. If in doubt, contact your local regulatory agency.

INTERNATIONAL REGULATIONS

Canada: Canadian Workplace Hazardous Materials Information System (WHMIS) – RCF is classified as Class D2A – Materials Causing Other Toxic Effects

Canadian Environmental Protection Act (CEPA) - All substances in this product are listed, as required, on the Domestic Substance List (DSL)

European Directive 97/69/EC classified RCF as a Category 2 carcinogen; that is it "should be regarded as if it is carcinogenic to man."

14. TRANSPORT INFORMATION

U.S. DEPARTMENT OF TRANSPORTATION (DOT)

Hazard Class:	Not Regulated	United Nations (UN) Number:	Not Applicable
Labels:	Not Applicable	North America (NA) Number:	Not Applicable
Placards:	Not Applicable	Product Name:	Bill of Lading;

INTERNATIONAL

Canada: TDG Hazard Class & PIN: Not regulated
Not classified as dangerous goods under ADR (road), RID (train) or IMDG (ship).

16. OTHER INFORMATION

RCF DEVITRIFICATION

As produced, all RCF fibers are vitreous (glassy) materials, which do not contain crystalline silica. Continued exposure to elevated temperatures may cause these fibers to devitrify (become crystalline). The first crystalline formation (mullite) begins to occur at approximately 985° C (1805° F). Crystalline phase silica may begin to form at temperatures of approximately 1200° C and temperature of exposure, fiber chemistry and/or the presence of fluxing agents. The presence of crystalline phases can be confirmed only through laboratory analysis of the "hot face" fiber.

Appendix - MSDS

IARC's evaluation of crystalline silica states "Crystalline silica inhaled in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (Group 1)" and additionally notes "carcinogenicity in humans was not detected in all industrial circumstances." Monograph Vol. 68, 1997). NTP lists all polymorphs of crystalline silica amongst substances which may "reasonably be anticipated to be carcinogens".

IARC and NTP did not evaluate after-service RCF, which may contain various crystalline phases. However, an analysis of after-service RCF samples obtained pursuant to an exposure monitoring agreement with the USEPA, found that in the furnace conditions sampled, most did not contain detectable levels of crystalline silica. Other relevant RCF studies found that (1) simulated after-service RCF showed little, or no, activity where exposure was by inhalation or by intraperitoneal injection; and (2) after-service RCF was not cytotoxic to macrophage-like cells at concentrations up to 320 g/cm^2 - by comparison, pure quartz or cristobalite were significantly active at much lower levels (circa 20 g/cm^2).

RCF AFTER-SERVICE REMOVAL

Respiratory protection should be provided in compliance with OSHA standards. During removal operations, a full face respirator is recommended to reduce inhalation exposure along with eye and respiratory tract irritation. A specific evaluation of workplace hazards and the identification of appropriate respiratory protection is best performed, on a case by case basis, by a qualified industrial hygiene professional.

PRODUCT STEWARDSHIP PROGRAM

The Unifrax Corporation has established a program to provide customers with up-to-date information regarding the proper use and handling of refractory ceramic fiber. In addition, Unifrax Corporation has also established a program to monitor airborne fiber concentrations at customer facilities. If you would like more information about this program, please call the Unifrax Corporation Product Stewardship Information Hotline at 1-800-322-2293.

On February 11, 2002, the Refractory Ceramic Fibers Coalition (RCFC) and the U.S. Occupational Safety and Health Administration (OSHA) introduced a voluntary worker protection program entitled PSP 2002, a comprehensive, multi-faceted risk management program designed to control and reduce workplace exposures to refractory ceramic fiber (RCF). Unifrax Corporation, as a member of RCFC, is participating in this highly acclaimed product stewardship program. For more information regarding PSP 2002, please call the Unifrax Corporation's Product Stewardship Information Hotline at 1-800-322-2293 or refer to the RCFC web site: <http://www.rcfc.net>.

DEFINITIONS

ACGIH: American Conference of Governmental Industrial Hygienists
ADR: Carriage of Dangerous Goods by Road (International Regulation)
CAA: Clean Air Act
CAS: Chemical Abstracts Service
CERCLA: Comprehensive Environmental Response, Compensation and Liability Act
DSL: Domestic Substances List
EPA: Environmental Protection Agency
EU: European Union
f/cc: Fibers per cubic centimeter
HEPA: High Efficiency Particulate Air
HMIS: Hazardous Materials Identification System
IARC: International Agency for Research on Cancer

DISCLAIMER

The information presented herein is presented in good faith and believed to be accurate as of the effective date of this Material Safety Data Sheet. Employers may use this MSDS to supplement other information gathered by them in their efforts to assure the health and safety of their employees and the proper use of the product. This summary of the relevant data reflects professional judgment; employers should note that information perceived to be less relevant has not been included in this MSDS. Therefore, given the summary nature of this document, Unifrax Corporation does not extend any warranty (expressed or implied), assume any responsibility, or make any representation regarding the completeness of this information or its suitability for the purposes envisioned by the user.

12.2 MSDS M0042 Fiberfrax® Duraboard®

OTHER POTENTIAL EFFECTS	
TARGET ORGANS:	Respiratory Tract (nose & throat), Eyes, Skin
RESPIRATORY TRACT (nose & throat) IRRITATION:	If inhaled in sufficient quantity, may cause temporary, mild mechanical irritation to respiratory tract. Symptoms may include scratchiness of the nose or throat, cough or chest discomfort.
EYE IRRITATION:	May cause temporary, mild mechanical irritation. Fibers may be abrasive; prolonged contact may cause damage to the outer surface of the eye.
SKIN IRRITATION:	May cause temporary, mild mechanical irritation. Exposure may also result in inflammation, rash or itching.
GASTROINTESTINAL IRRITATION:	Unlikely route of exposure.
MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:	Pre-existing medical conditions, including dermatitis, asthma or chronic lung disease may be aggravated by exposure; individuals who have a history of allergies may experience greater amounts of skin and respiratory irritation.

MATERIAL SAFETY DATA SHEET	
MSDS No. M0042	Effective Date: 03/09/2004
1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION	
Product Group:	REFRACTORY CERAMIC FIBER PRODUCT
Chemical Name:	VITREOUS ALUMINOSILICATE FIBER
Synonym(s):	RCF ceramic fiber; synthetic vitreous fiber (SVF); man-made vitreous fiber (MMVF); man-made mineral fiber (MMMF)
Trade Names:	FIBERFRAX® DURABOARD® LD
Manufacturer/Supplier:	Unifrax Corporation Duraboard® LD, Duraboard® LD-RG, Duraboard® LD-HT 2354 Whirlpool St. Niagara Falls, NY 14305-2413
Product Stewardship Information Hotline 1-800-322-2293 (Monday - Friday 8:00 a.m. - 4:30 p.m. EST)	For additional MSDSs, visit our web page, http://www.unifrax.com , or call Unifrax Customer Service at (716) 278-3872
CHEMTREC Assist:	CHEMTREC will provide assistance for chemical emergencies. Call 1-800-424-9300
2. COMPOSITION / INFORMATION ON INGREDIENTS	
COMPONENTS	GAS NUMBER % BY WEIGHT
Refractories, Fibers, Aluminosilicate	142844-00-6 70-85
Silica (amorphous)	112926-00-8 10-15
Starch	9005-25-8 5-10
	(See Section 8 "Exposure Controls / Personal Protection" for exposure guidelines)
3. HAZARDS IDENTIFICATION	
EMERGENCY OVERVIEW	
WARNING!	POSSIBLE CANCER HAZARD BY INHALATION. (See Section 11 for more information)
CHRONIC EFFECT	
	There has been no increased incidence of respiratory disease in studies examining occupationally exposed workers. In animal studies, long-term laboratory exposure to doses hundreds of times higher than normal occupational exposures has produced fibrosis, lung cancer, and mesothelioma in rats or hamsters. The fibers used in those studies were specially sized to maximize rodent respirability.

Appendix - MSDS

The Canadian Environmental Protection Agency (CEPA) has classified RCF as "probably carcinogenic" (Group 2).

The Canadian Workplace Hazardous Materials Information System (WHMIS) – RCF is classified as Class D2A – Materials Causing Other Toxic Effects

The Hazardous Materials Identification System (HMIS) –

Health 1*	Flammability 0	Reactivity 0	Personal Protection Index: X (Employer Determined)
-----------	----------------	--------------	--

(* denotes potential for chronic effects)

4. FIRST AID MEASURES

FIRST AID PROCEDURES

RESPIRATORY TRACT (nose & throat) IRRITATION:

If respiratory tract irritation develops, move the person to a dust free location. Get medical attention if the irritation continues. See Section 8 for additional measures to reduce or eliminate exposure.

EYE IRRITATION:

If eyes become irritated, flush immediately with large amounts of lukewarm water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Do not rub eyes. Get medical attention if irritation persists.

SKIN IRRITATION:

If skin becomes irritated, remove soiled clothing. Do not rub or scratch exposed skin. Wash area of contact thoroughly with soap and water. Using a skin cream or lotion after washing may be helpful.

GASTROINTESTINAL IRRITATION:

If gastrointestinal tract irritation develops, move the person to a dust free environment.

NOTES TO PHYSICIANS:

Skin and respiratory effects are the result of temporary, mild mechanical irritation; fiber exposure does not result in allergic manifestations.

5. FIRE FIGHTING MEASURES

NFPA Codes:

Flammability: 0 Health: 1 Reactivity: 0 Special: 0

6. ACCIDENTAL RELEASE MEASURES

SPILL PROCEDURES

Avoid creating airborne dust. Dust suppressing cleaning methods such as wet sweeping or vacuuming should be used to clean the work area. If vacuuming, the vacuum must be equipped with a HEPA filter. Compressed air or dry sweeping should not be used for cleaning.

7. HANDLING AND STORAGE

STORAGE

Store in original container in a dry area. Keep container closed when not in use.

HANDLING

Handle ceramic fiber carefully. Limit use of power tools unless in conjunction with local exhaust. Use hand tools whenever possible. Frequently clean the work area with HEPA filtered vacuum or wet sweeping to minimize the accumulation of debris. Do not use compressed air for clean-up.

EMPTY CONTAINERS

Product packaging may contain residue. Do not reuse.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE GUIDELINES – RCF

COMPONENTS	OSHA PEL	MANUFACTURER REG
Refractories, Fibers, Aluminosilicate	None Established*	0.5 f/cc, 8-hr. TWA**

* There is no specific regulatory standard for RCF in the U.S. OSHA's "Particulate Not Otherwise Regulated (PNOR)" standard [29 CFR 1910.1000, Subpart Z, Air Contaminants] applies generally; Total Dust 15 mg/m³, Respirable Fraction 5 mg/m³.

** The Refractory Ceramic Fibers Coalition (RCFC) has sponsored comprehensive toxicology and

Chapter 12

epidemiology studies to identify potential RCF-related health effects [see Section 11 for more details], consulted experts familiar with fiber and particle science, conducted a thorough review of the RCF-related scientific literature, and further evaluated the data in a state-of-the-art quantitative risk assessment. Based on these efforts and in the absence of an OSHA PEL, RCF has adopted a recommended exposure guideline, as measured under NIOSH Method 7400 B. The manufacturer's REG is intended to promote occupational health and safety through prudent exposure control and reduction and it reflects relative technical and economic feasibility as determined by extensive industrial hygiene monitoring efforts undertaken pursuant to an agreement with the U.S. Environmental Protection Agency.

OTHER OCCUPATIONAL EXPOSURE LEVELS (OEL)

RCF-related occupational exposure limits vary internationally. Regulatory OEL examples include: Australia – 0.5 f/cc; Austria – 0.5 f/cc; Canada – 0.5 to 1.0 f/cc; Denmark – 1.0 f/cc; France – 0.6 f/cc; Germany – 0.5 f/cc; Netherlands – 1.0 f/cc; New Zealand – 1.0 f/cc; Norway – 2.0 f/cc; Poland – 2.0 f/cc; Sweden – 1.0 f/cc; United Kingdom – 2.0 f/cc. Non-regulatory OEL examples include: ACGIH TLV 0.5 f/cc; RCFC REG 0.2 f/cc. The objectives and criteria underlying each of these OEL decisions also vary. The evaluation of occupational exposure limits and determining their relative applicability to the workplace is best performed, on a case-by-case basis, by a qualified Industrial Hygienist.

EXPOSURE GUIDELINES -- OTHER INGREDIENTS

COMPONENTS	OSHA PEL	MANUFACTURER REG
Silica (amorphous) Starch	20 mppcf or 80 mg/m ³ / % SiO ₂ 5 mg/m ³ PEL (resp. dust) 15 mg/m ³ PEL (total dust)	None established None established

OTHER OCCUPATIONAL EXPOSURE LEVELS (OEL)

Non-regulatory OEL examples include: ACGIH TLVs (TWAs): Silica (amorphous) -- 10 mg/m³. Starch -- 10 mg/m³.

ENGINEERING CONTROLS
Use engineering controls such as local exhaust ventilation, point of generation dust collection, down draft work stations, emission controlling tool designs, and materials handling equipment designed to minimize airborne fiber emissions.

PERSONAL PROTECTION EQUIPMENT

Respiratory Protection – RCF:

When engineering and/or administrative controls are insufficient to maintain workplace concentrations within the 0.5 f/cc REG, the use of appropriate respiratory protection, pursuant to the requirements of OSHA Standards 29 CFR 1910.134 and 29 CFR 1926.103, is recommended. The following information is provided as an example of appropriate respiratory protection for aluminosilicate fibers. The evaluation of workplace hazards and the identification of appropriate

respiratory protection is best performed, on a case by case basis, by a qualified Industrial Hygienist.

MANUFACTURER'S RESPIRATORY PROTECTION RECOMMENDATIONS WHEN HANDLING RCF PRODUCTS	
Respirable Airborne Fiber Concentration (Levels are 8-hr. time-weighted averages)	Respirator Recommendation [†]
Not yet determined but expected to be below 5.0 f/cc based on operation	Half-face, air purifying respirator equipped with a NIOSH certified P100 particulate filter cartridge
"Reliably" [‡] less than 0.5 f/cc	Optional
0.5 f/cc to 5.0 f/cc	Half-face, air purifying respirator equipped with a NIOSH certified P100 particulate filter cartridge
5.0 f/cc to 25 f/cc	Full-facepiece, air purifying respirator equipped with a NIOSH certified P100 particulate filter cartridge or PAPR
Greater than 25 f/cc	PAPR with tight-fitting full facepiece or a supplied air respirator in continuous flow mode
When individual workers request respiratory protection as a matter of personal comfort or choice where exposures are "reliably" below 0.5 f/cc	A NIOSH certified respirator, such as a disposable particulate respirator, or respirators with filter cartridges rated N95 or better

[†]The P100 recommendation is a conservative default choice; in some cases, solid arguments can be made that other respirator types (e.g., N95, R99, etc.) may be suitable for some tasks or work environments. The P100 recommendation is not designed to limit informed choices, provided that respiratory protection decisions comply with 29 CFR 1910.134.

Other Information:

- Concentrations based upon an eight-hour time weighted average (TWA) as determined by air samples collected and analyzed pursuant to NIOSH method 7400 (B) for airborne fibers.
- The manufacturer recommends the use of a full-facepiece air purifying respirator equipped with an appropriate particulate filter cartridge during furnace tear-out events and the removal of used RCF to control exposures to airborne fiber and the potential presence of crystalline silica. If exposure levels are known, the respiratory protection chart provided above may be applied.
- Potential exposure to other airborne contaminants should be evaluated by a qualified Industrial Hygienist for the selection of appropriate respiratory protection and air monitoring.

Skin Protection:

Wear gloves, head coverings and full body clothing as necessary to prevent skin irritation. Washable or disposable clothing may be used. If possible, do not take unwashed clothing home.

Appendix - MSDS

If soiled work clothing must be taken home, employers should ensure employees are thoroughly trained on the best practices to minimize or avoid non-work dust exposure (e.g., vacuum clothes before leaving the work area, wash work clothing separately, rinse washer before washing other household clothes, etc.).

Eye Protection:

Wear safety glasses with side shields or other forms of eye protection in compliance with appropriate OSHA standards to prevent eye irritation. The use of contact lenses is not recommended, unless used in conjunction with appropriate eye protection. Do not touch eyes with soiled body parts or materials. If possible, have eye-washing facilities readily available where eye irritation can occur.

9. PHYSICAL AND CHEMICAL PROPERTIES

ODOR AND APPEARANCE:	White, odorless, fibrous material
CHEMICAL FAMILY:	Vitreous Aluminosilicate Fibers
BOILING POINT:	Not Applicable
WATER SOLUBILITY (%):	Not Soluble in Water
MELTING POINT:	1760° C (3200° F)
SPECIFIC GRAVITY:	2.50 – 2.75
VAPOR PRESSURE:	Not Applicable
pH:	Not Applicable
VAPOR DENSITY (Air = 1):	Not Applicable
% VOLATILE:	Not Applicable
MOLECULAR FORMULA:	Not Applicable

10. STABILITY AND REACTIVITY

Stable under conditions of normal use.
Soluble in hydrofluoric acid, phosphoric acid, and concentrated alkali.
None.
Thermal decomposition of binder from fires or from first heat of product may release smoke, carbon monoxide, and carbon dioxide. Use adequate ventilation or other precautions to eliminate exposure to vapors resulting from thermal decomposition of binder. Exposure to thermal decomposition fumes may cause respiratory tract irritation, bronchial hyper-reactivity or an asthmatic-type response.
Not Applicable.

11. TOXICOLOGICAL INFORMATION

HEALTH DATA SUMMARY

Epidemiological studies of RCF production workers have indicated no increased incidence of respiratory disease nor other significant health effects. In animal studies, long-term, high-dose inhalation exposure resulted in the development of respiratory disease in rats and hamsters.

EPIDEMIOLOGY

The University of Cincinnati is conducting an ongoing epidemiologic investigation. The evidence obtained from employees in U. S. RCF manufacturing facilities is as follows:

- 1) There is no evidence of any fibrotic lung disease (interstitial fibrosis) from evaluations of chest X-rays.
- 2) There is no evidence of an elevated incidence of lung disease among RCF manufacturing employees.
- 3) In early studies, an apparent statistical "trend" was observed, in the exposed population, between RCF exposure duration and some measures of lung function. The observations were clinically insignificant. If these observations were made on an individual employee, the results would be interpreted as being within the normal (predicted) respiratory range. A more recent longitudinal study of employees with 5 or more pulmonary function tests found that there was no effect on lung function associated with RCF production experience. Initial data (circa 1987) seemed to indicate an interactive effect between smoking and RCF exposure; more recent data, however, found no interactive effect. Nevertheless, to promote good health, RCF employees are still actively encouraged not to smoke.
- 4) Pleural plaques (thickening along the chest wall) have been observed in a small number of RCF employees. Some studies appear to show a relationship between the occurrence of pleural plaques on chest radiographs and the following variables: (a) years since RCF production hire date, (b) duration of RCF production employment; and (c) cumulative RCF exposure. The best evidence to date indicates that pleural plaques are a marker of exposure only. Pleural plaques are not associated with pulmonary impairment. The pathogenesis of pleural plaques remains incompletely understood; however, the mechanism appears to be an inflammatory response caused by inhaled fibers.

TOXICOLOGY

A number of toxicological studies designed to identify any potential health effects from RCF exposure have been completed. In one study, conducted by the Research and Consulting Company (Geneva, Switzerland), rats and hamsters were exposed to 30 mg/m³ (about 200 fibers/cc) of specially-prepared RCF for 6 hours/day, 5 days/week, for up to 24 months. In rats, a statistically significant increase in lung tumors was observed; two mesotheliomas (cancer of the pleural lining between the chest wall and lung) were also identified. Hamsters did not develop lung tumors; however, interstitial fibrosis and mesothelioma was found. Some, in the scientific community, have concluded that the "maximum tolerated dose" was exceeded and that significant particle contamination was a confounding issue; therefore, these study findings may not represent an accurate assessment of the potential for RCF to produce adverse health effects.

In a related multi-dose study with a similar protocol, other rats were exposed to doses of 16 mg/m³, 9 mg/m³, 3 mg/m³ which corresponds to about 115, 75, and 25 fibers per cubic centimeter respectively. This study found no statistically significant increase in lung cancer. Some cases of pleural and parenchymal fibrosis were seen in the 16 mg/m³ dose group. Some cases of mild fibrosis and one mesothelioma were observed in the 9 mg/m³ group. No acute respiratory effects were seen in the rats in the 3 mg/m³ exposure group, which suggests that there may be a dose/response threshold, below which irreversible respiratory impacts do not occur.

Other toxicological studies have been conducted which utilized non-physiological exposure methods such as intrapleural, intraperitoneal and intratracheal implantation or injection. Some of these studies have found that RCF is a potential carcinogen. Some experts, however, suggest

Chapter 12

that these tests have limited relevance because they bypass many of the biological mechanisms that prevent fiber deposition or facilitate fiber clearance.

To obtain more epidemiology or toxicology information, please call the toll free telephone number for the Unifrax Corporation Product Stewardship Program found in Section 16 - Other Information.

12. ECOLOGICAL INFORMATION

No ecological concerns have been identified.

13. DISPOSAL CONSIDERATIONS

WASTE MANAGEMENT

To prevent waste materials from becoming airborne during waste storage, transportation and disposal, a covered container or plastic bagging is recommended.

DISPOSAL

RCF, as manufactured, is not classified as a hazardous waste according to Federal regulations (40 CFR 261). Any processing, use, alteration or chemical additions to the product, as purchased, may alter the disposal requirements. Under Federal regulations, it is the waste generator's responsibility to properly characterize a waste material to determine if it is a "hazardous" waste. Check local, regional, state or provincial regulations to identify all applicable disposal requirements.

14. TRANSPORT INFORMATION

U.S. DEPARTMENT OF TRANSPORTATION (DOT)

Hazard Class: Not Regulated
Labels: Not Applicable
Placards: Not Applicable

United Nations (UN) Number: Not Applicable
North America (NA) Number: Not Applicable
Bill of Lading:

INTERNATIONAL

Canadian TDG Hazard Class & PIN: Not regulated
Not classified as dangerous goods under ADR (road), RID (train) or IMDG (ship).

15. REGULATORY INFORMATION

UNITED STATES REGULATIONS

EPA: Superfund Amendments and Reauthorization Act (SARA) Title III - This product does not contain any substances reportable under Sections 302, 304, 313, (40 CFR 372). Sections 311 and 312 (40 CFR 370) apply (delayed hazard).

Toxic Substances Control Act (TSCA) - All substances in this product are listed, as required, on the TSCA inventory. RCF has been assigned a CAS number; however, it is a simple mixture and therefore not required to be listed on the TSCA inventory. The components of RCF are listed on the inventory.

Comprehensive Environmental Response, Compensation and Liability Act (CERCLA) and the Clean Air Act (CAA) - RCF contains fibers with an average diameter greater than one micron and thus is not considered a hazardous air pollutant.

Comply with Hazard Communication Standards 29 CFR 1910.1200 and 29 CFR 1926.59 and the Respiratory Protection Standards 29 CFR 1910.134 and 29 CFR 1926.103.

Ceramic fibers (airborne particles of respirable size)" is listed in Proposition 65, The Safe Drinking Water and Toxic Enforcement Act of 1986 as a chemical known to the State of California to cause cancer.

RCF products are not known to be regulated by states other than California; however, state and local OSHA and EPA regulations may apply to these products. If in doubt, contact your local regulatory agency.

INTERNATIONAL REGULATIONS

OSHA: Canadian Workplace Hazardous Materials Information System (WHMIS) – RCF is classified as Class D2A – Materials Causing Other Toxic Effects

Canadian Environmental Protection Act (CEPA) - All substances in this product are listed, as required, on the Domestic Substance List (DSL)

European Directive 97/68/EC classified RCF as a Category 2 carcinogen; that is it "should be regarded as if it is carcinogenic to man."

16. OTHER INFORMATION

RCF DEVITRIFICATION

As produced, all RCF fibers are vitreous (glassy) materials which do not contain crystalline silica. Continued exposure to elevated temperatures may cause these fibers to devitrify (become crystalline). The first crystalline formation (mullite) begins to occur at approximately 985° C (1805° F). Crystalline phase silica may begin to form at temperatures of approximately 1200° C (2192° F). The occurrence and extent of crystalline phase formation is dependent on the duration and temperature of exposure, fiber chemistry and/or the presence of fluxing agents. The presence of crystalline phases can be confirmed only through laboratory analysis of the "hot face" fiber.

IARC's evaluation of crystalline silica states "Crystalline silica inhaled in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (Group 1)" and additionally notes "carcinogenicity in humans was not detected in all industrial circumstances studied" (IARC Monograph Vol. 68, 1997). NTP lists all polymorphs of crystalline silica amongst substances which may "reasonably be anticipated to be carcinogens".

IARC and NTP did not evaluate after-service RCF, which may contain various crystalline phases. However, an analysis of after-service RCF samples obtained pursuant to an exposure monitoring agreement with the USEPA, found that in the furnace conditions sampled, most did not contain detectable levels of crystalline silica. Other relevant RCF studies found that (1) simulated after-service RCF showed little, or no, activity where exposure was by inhalation or by intraperitoneal

Appendix - MSDS

injection; and (2) after-service RCF was not cytotoxic to macrophage-like cells at concentrations up to 320 g/cm² - by comparison, pure quartz or cristobalite were significantly active at much lower levels (circa 20 g/cm²).

RCF AFTER-SERVICE REMOVAL

Respiratory protection should be provided in compliance with OSHA standards. During removal operations, a full face respirator is recommended to reduce inhalation exposure along with eye and respiratory tract irritation. A specific evaluation of workplace hazards and the identification of appropriate respiratory protection is best performed, on a case by case basis, by a qualified industrial hygiene professional.

PRODUCT STEWARDSHIP PROGRAM

The Unifrax Corporation has established a program to provide customers with up-to-date information regarding the proper use and handling of refractory ceramic fiber. In addition, Unifrax Corporation has also established a program to monitor airborne fiber concentrations at customer facilities. If you would like more information about this program, please call the Unifrax Corporation Product Stewardship Information Hotline at 1-800-322-2293.

On February 11, 2002, the Refractory Ceramic Fibers Coalition (RCFC) and the U.S. Occupational Safety and Health Administration (OSHA) introduced a voluntary worker protection program entitled PSP 2002, a comprehensive, multi-faceted risk management program designed to control and reduce workplace exposures to refractory ceramic fiber (RCF). Unifrax Corporation, as a member of RCFC, is participating in this highly acclaimed product stewardship program. For more information regarding PSP 2002, please call the Unifrax Corporation's Product Stewardship Information Hotline at 1-800-322-2293 or refer to the RCFC web site: <http://www.rcfc.net>.

DEFINITIONS

ACGIH:	American Conference of Governmental Industrial Hygienists
ADR:	Carriage of Dangerous Goods by Road (International Regulation)
CAA:	Clean Air Act
CAS:	Chemical Abstracts Service
CERCLA:	Comprehensive Environmental Response, Compensation and Liability Act
DSL:	Domestic Substances List
EPA:	Environmental Protection Agency
EU:	European Union
FCC:	Fibers per cubic centimeter
HEPA:	High Efficiency Particulate Air
HMIS:	Hazardous Materials Identification System
IARC:	International Agency for Research on Cancer
ITATA:	International Air Transport Association
IMDG:	International Maritime Dangerous Goods Code
mg/m ³ :	Milligrams per cubic meter of air
mmpcf:	Million particles per cubic meter
NFPA:	National Fire Protection Association
NIOSH:	National Institute for Occupational Safety and Health
OSHA:	Occupational Safety and Health Administration
29 CFR 1910.134 &	OSHA Respiratory Protection Standards
1926.103:	
29 CFR 1910.1200 &	
1926.59:	

PEL:	Permissible Exposure Limit (OSHA)
PIN:	Product Identification Number
PNOC:	Particulates Not Otherwise Classified
PNOR:	Particulates Not Otherwise Regulated
PSP:	Product Stewardship Program
RCFC:	Refractory Ceramic Fibers Coalition
RORA:	Resource Conservation and Recovery Act
REG:	Recommended Exposure Guideline (RCFC)
REL:	Recommended Exposure Limit (NIOSH)
RID:	Carriage of Dangerous Goods by Rail (International Regulations)
SARA:	Superfund Amendments and Reauthorization Act
SARA Title III:	Emergency Planning and Community Right to Know Act
SARA Section 302:	Extremely Hazardous Substances
SARA Section 304:	Emergency Release
SARA Section 311:	MSDS/List of Chemicals and Hazardous Inventory
SARA Section 312:	Emergency and Hazardous Inventory
SARA Section 313:	Toxic Chemicals and Release Reporting
STEL:	Short Term Exposure Limit
SVF:	Synthetic Vitreous Fiber
TDG:	Transportation of Dangerous Goods
TLV:	Threshold Limit Value (ACGIH)
TSCA:	Toxic Substances Control Act
TWA:	Time Weighted Average
WHMIS:	Workplace Hazardous Materials Information System (Canada)
Revision Summary:	Minor modification to devitrification section. Replaces 2/11/02 MSDS.
MSDS Prepared By:	UNIFRAX RISK MANAGEMENT DEPARTMENT

DISCLAIMER

The information presented herein is presented in good faith and believed to be accurate as of the effective date of this Material Safety Data Sheet. Employers may use this MSDS to supplement other information gathered by them in their efforts to assure the health and safety of their employees and the proper uses of the product. This summary of the relevant data reflects professional judgment; employers should note that information perceived to be less relevant has not been included in this MSDS. Therefore, given the summary nature of this document, Unifrax Corporation does not extend any warranty (expressed or implied), assume any responsibility, or make any representation regarding the completeness of this information or its suitability for the purposes envisioned by the user.

12.3 Fiberfrax® Refractory Ceramic Fiber MSDS 0001

3. HAZARDS IDENTIFICATION	
EMERGENCY OVERVIEW	
WARNING!	POSSIBLE CANCER HAZARD BY INHALATION. (See Section 11 for more information)
CHRONIC EFFECT There has been no increased incidence of respiratory disease in studies examining occupationally exposed workers. In animal studies, long-term laboratory exposure to doses hundreds of times higher than normal occupational exposures has produced fibrosis, lung cancer, and mesothelioma in rats or hamsters. The fibers used in those studies were specially sized to maximize rodent respirability.	OTHER POTENTIAL EFFECTS TARGET ORGANS: Respiratory Tract (nose & throat), Eyes, Skin RESPIRATORY TRACT (nose & throat) IRRITATION: If inhaled in sufficient quantity, may cause temporary, mild mechanical irritation to respiratory tract. Symptoms may include scratchiness of the nose or throat, cough or chest discomfort. EYE IRRITATION: May cause temporary, mild mechanical irritation. Fibers may be abrasive; prolonged contact may cause damage to the outer surface of the eye. SKIN IRRITATION: May cause temporary, mild mechanical irritation. Exposure may also result in inflammation, rash or itching. GASTROINTESTINAL IRRITATION: Unlikely route of exposure. MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Pre-existing medical conditions, including dermatitis, asthma or chronic lung disease may be aggravated by exposure, individuals who have a history of allergies may experience greater amounts of skin and respiratory irritation.
FIBERS FIBERFRAX® HIGH PURITY FIBERS: HP-O'DB, Module Trim, MT-HP, HP-Chopped, H Bulk, Regular Bulk, Spun Bulk, Fiberfrax FFP Fiber. FIBERFRAX® 6000 SERIES FIBERS: All bulk fibers from 6000-AAA to 6100-ZZZ, 6900-70A to 900-99Z. FIBERFRAX® 7000 SERIES FIBERS: 7000-AA to 7100-ZZ. FIBERFRAX® MILLED FIBERS: EF-119, HP Ball Milled A; HP Ball Milled B; HP Ball Milled C/D FIBERFRAX® HIGH INDEX FIBERS: W-65T, W-70T, W-75B, HS-95C, MX-135-CW, MX-400-CW, HS-70, HS-70C. FIBERFRAX® HSA™ FIBERS: HSA-K; HSA-HP. FIBERFRAX® KAOLIN FIBERS: K-Chopped; KMTX; MT; MTX; MT-T; MX-150.	BLANKETS Durablanket® AC; Durablanket® HP; Durablanket® HP-S; Durablanket® S; Durablanket® Strip; Duraback®; Duraback® S; Tank Car Insulation; TCB; SMB; QSB600; QSB800; FIBERMAT®; LO-CON™ BLANKET
PAPERS FIBERFRAX® BINDERLESS PAPERS: 972-AH, 972-FH, 972-JH, 882-FH; 882-JH; HSA-J without binder; HSA-J without binder.	Manufacturer/Supplier: Unifrax Corporation 2351 Whirlpool St. Niagara Falls, NY 14305-2413 Product Stewardship Information Hotline 1-800-322-2293 (Monday - Friday 8:00 a.m. - 4:30 p.m. EST) For additional MSDSs, visit our web page, http://www.unifrax.com, or call Unifrax Customer Service at (716) 278-3872
CHEMTRAC Assist: CHEMTRAC will provide assistance for chemical emergencies. Call 1-800-424-9300	HAZARD CLASSIFICATION Although studies, involving occupationally exposed workers, have not identified any increased incidence of respiratory disease, results from animal testing have been used as the basis for

MATERIAL SAFETY DATA SHEET	
Effective Date: 03/09/2004	
MSDS No. M0001	
Product Group: Chemical Name: Synonym(s):	VITREOUS ALUMINOSILICATE FIBER RCF - ceramic fiber, synthetic vitreous fiber (SVF), man-made vitreous fiber (MMVF), man-made mineral fiber (MMMF)
Trade Names:	FIBERFRAX® CERAMIC FIBER PRODUCTS , INCLUDES:
FIBERS	FIBERFRAX® HIGH PURITY FIBERS: HP-O'DB, Module Trim, MT-HP, HP-Chopped, H Bulk, Regular Bulk, Spun Bulk, Fiberfrax FFP Fiber. FIBERFRAX® 6000 SERIES FIBERS: All bulk fibers from 6000-AAA to 6100-ZZZ, 6900-70A to 900-99Z. FIBERFRAX® 7000 SERIES FIBERS: 7000-AA to 7100-ZZ. FIBERFRAX® MILLED FIBERS: EF-119, HP Ball Milled A; HP Ball Milled B; HP Ball Milled C/D FIBERFRAX® HIGH INDEX FIBERS: W-65T, W-70T, W-75B, HS-95C, MX-135-CW, MX-400-CW, HS-70, HS-70C. FIBERFRAX® HSA™ FIBERS: HSA-K; HSA-HP. FIBERFRAX® KAOLIN FIBERS: K-Chopped; KMTX; MT; MTX; MT-T; MX-150.
PAPERS	FIBERFRAX® BINDERLESS PAPERS: 972-AH, 972-FH, 972-JH, 882-FH; 882-JH; HSA-J without binder; HSA-J without binder.
Manufacturer/Supplier:	Unifrax Corporation 2351 Whirlpool St. Niagara Falls, NY 14305-2413 Product Stewardship Information Hotline 1-800-322-2293 (Monday - Friday 8:00 a.m. - 4:30 p.m. EST) For additional MSDSs, visit our web page, http://www.unifrax.com, or call Unifrax Customer Service at (716) 278-3872
2. COMPOSITION / INFORMATION ON INGREDIENTS	
COMPONENTS	CAS NUMBER
Refractories, Fibers, Aluminosilicate	142844-00-6
(See Section 8 "Exposure Controls / Personal Protection" for exposure guidelines)	100

Appendix - MSDS

hazard classification. In each of the following cases, the conclusions are qualitative only and do not rest upon any quantitative analysis suggesting that the hazard actually may occur at current occupational exposure levels.

In October 2001, the International Agency for Research on Cancer (IARC) confirmed that Group 2b (possible human carcinogen) remains the appropriate IARC classification for RCF.

The Seventh Annual Report on Carcinogens (1994), prepared by the National Toxicology Program (NTP), classified respirable RCF and glasswool as substances reasonably anticipated to be carcinogens.

The American Conference of Governmental Industrial Hygienists (ACGIH) has classified RCF as "A2-Suspected Human Carcinogen."

The Commission of The European Communities (DG XI) has classified RCF as a substance that should be regarded as if it is carcinogenic to man.

The State of California, pursuant to Proposition 65, "The Safe Drinking Water and Toxic Enforcement Act of 1986, has listed "ceramic fibers (airborne fibers of respirable size)" as a chemical known to the State of California to cause cancer.

The Canadian Environmental Protection Agency (CEPA) has classified RCF as "probably carcinogenic" (Group 2).

The Canadian Workplace Hazardous Materials Information System (WHMIS) – RCF is classified as Class D2A – Materials Causing Other Toxic Effects

The Hazardous Materials Identification System (HMIS) –

Health 1* Flammability 0 Reactivity 0 Personal Protection Index: X (Employer Determined)

(* denotes potential for chronic effects)

of contact thoroughly with soap and water. Using a skin cream or lotion after washing may be helpful.

GASTROINTESTINAL IRRITATION:
If gastrointestinal tract irritation develops, move the person to a dust free environment.

NOTES TO PHYSICIANS:

Skin and respiratory effects are the result of temporary, mild mechanical irritation; fiber exposure does not result in allergic manifestations.

5. FIRE FIGHTING MEASURES

NFPA Codes: Flammability: 0 Health: 1 Reactivity: 0 Special: 0

NFPA Unusual Hazards: None
Flammable Properties: None
Flash Point: None
Hazardous Decomposition Products: None
Unusual Fire and Explosion Hazard: None
Extinguishing Media: Use extinguishing media suitable for type of surrounding fire.

6. ACCIDENTAL RELEASE MEASURES

SPILL PROCEDURES

Avoid creating airborne dust. Dust suppressing cleaning methods such as wet sweeping or vacuuming should be used to clean the work area. If vacuuming, the vacuum must be equipped with a HEPA filter. Compressed air or dry sweeping should not be used for cleaning.

4. FIRST AID MEASURES

FIRST AID PROCEDURES

RESPIRATORY TRACT (nose & throat) IRRITATION:

If respiratory tract irritation develops, move the person to a dust free location. Get medical attention if the irritation continues. See Section 8 for additional measures to reduce or eliminate exposure.

EYE IRRITATION:

If eyes become irritated, flush immediately with large amounts of lukewarm water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Do not rub eyes. Get medical attention if irritation persists.

SKIN IRRITATION:

If skin becomes irritated, remove soiled clothing. Do not rub or scratch exposed skin. Wash area

7. HANDLING AND STORAGE

STORAGE

Store in original container in a dry area. Keep container closed when not in use.

HANDLING

Handle ceramic fiber carefully. Limit use of power tools unless in conjunction with local exhaust. Use hand tools whenever possible. Frequently clean the work area with HEPA filtered vacuum or wet sweeping to minimize the accumulation of debris. Do not use compressed air for clean-up.

EMPTY CONTAINERS

Product packaging may contain residue. Do not reuse.

Chapter 12

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE GUIDELINES	
COMPONENTS	OSHA PEL
Refractories Fibers, Aluminosilicate	None Established*

* There is no specific regulatory standard for RCF in the U.S. OSHA's "Particulate Not Otherwise Regulated (PNOR)" standard [29 CFR 1910.1000, Subpart Z, Air Contaminants] applies generally: Total Dust 15 mg/m³; Respirable Fraction 5 mg/m³.

** The Refractory Ceramic Fibers Coalition (RCFC) has sponsored comprehensive toxicology and epidemiology studies to identify potential RCF-related health effects [see Section 11 for more details], consulted experts familiar with fiber and particle science, conducted a thorough review of the RCF-related scientific literature, and further evaluated the data in a state-of-the-art quantitative risk assessment. Based on these efforts and in the absence of an OSHA PEL, RCFC has adopted a recommended exposure guideline, as measured under NIOSH Method 7400 B. The manufacturers' REG is intended to promote occupational health and safety through prudent exposure control and reduction and it reflects relative technical and economic feasibility as determined by extensive industrial hygiene monitoring efforts undertaken pursuant to an agreement with the U.S. Environmental Protection Agency.

OTHER OCCUPATIONAL EXPOSURE LEVELS (OEL)

RCF-related occupational exposure limits vary internationally. Regulatory OEL examples include: Australia – 0.5 f/cc; Austria – 0.5 f/cc; Canada – 0.5 to 1.0 f/cc; Denmark – 1.0 f/cc; France – 0.6 f/cc; Germany – 0.5 f/cc; Netherlands – 1.0 f/cc; New Zealand – 1.0 f/cc; Norway – 2.0 f/cc; Poland – 2.0 f/cc; Sweden – 1.0 f/cc; United Kingdom – 2.0 f/cc. Non-regulatory OEL examples include: ACGIH TLV 0.2 f/cc; RCFC REG 0.5 f/cc. The objectives and criteria underlying each of these OEL decisions also vary. The evaluation of occupational exposure limits and determining their relative applicability to the workplace is best performed, on a case-by-case basis, by a qualified Industrial Hygienist.

ENGINEERING CONTROLS

Use engineering controls such as local exhaust ventilation, point of generation dust collection, down draft work stations, emission controlling tool designs, and materials handling equipment designed to minimize airborne fiber emissions.

PERSONAL PROTECTION EQUIPMENT

Respiratory Protection – RCF:

When engineering and/or administrative controls are insufficient to maintain workplace concentrations within the 0.5 f/cc REG, the use of appropriate respiratory protection, pursuant to the requirements of OSHA Standards 29 CFR 1910.134 and 29 CFR 1926.103, is recommended. The following information is provided as an example of appropriate respiratory protection for alumino-silicate fibers. The evaluation of workplace hazards and the identification of appropriate respiratory protection is best performed, on a case by case basis, by a qualified Industrial Hygienist.

MANUFACTURER'S RESPIRATORY PROTECTION RECOMMENDATIONS WHEN HANDLING RCF PRODUCTS	
Respirable Airborne Fiber Concentration (levels are 8-hr. time-weighted averages)	Respirator Recommendation [†]
Not yet determined but expected to be below 5.0 f/cc based on operation	Half-face, air purifying respirator equipped with a NIOSH certified P100 particulate filter cartridge
"Reliable" less than 0.5 f/cc	Optional
0.5 f/cc to 5.0 f/cc	Half-face, air purifying respirator equipped with a NIOSH certified P100 particulate filter cartridge
5.0 f/cc to 25 f/cc	Full-facepiece, air purifying respirator equipped with a NIOSH certified P100 particulate filter cartridge or PAPR
Greater than 25 f/cc	PAPR with tight-fitting full facepiece or a supplied air respirator in continuous flow mode
When individual workers request respiratory protection as a matter of personal comfort or choice where exposures are "reliably" below 0.5 f/cc	A NIOSH certified respirator, such as a disposable particulate respirator, or respirators with filter cartridges rated N95 or better

[†]The P100 recommendation is a conservative default choice, in some case, solid arguments can be made that other respirator types (e.g., N95, R95, etc.) may be suitable for some tasks or work environments. The P100 recommendation is not designed to limit informed choices, provided that respiratory protection decisions comply with 29 CFR 1910.134.

Other Information:

- Concentrations based upon an eight-hour time weighted average (TWA) as determined by air samples collected and analyzed pursuant to NIOSH method 7400 (B) for airborne fibers.
- The manufacturer recommends the use of a full-facepiece air purifying respirator equipped with an appropriate particulate filter cartridge during furnace tear-out events and the removal of used RCF to control exposures to airborne fiber and the potential presence of crystalline silica. If exposure levels are known, the respiratory protection chart provided above may be applied.
- Potential exposure to other airborne contaminants should be evaluated by a qualified Industrial Hygienist for the selection of appropriate respiratory protection and air monitoring.

Skin Protection:

Wear gloves, head coverings and full body clothing as necessary to prevent skin irritation. Washable or disposable clothing may be used. If possible, do not take unwashed clothing home.

Appendix - MSDS

If soiled work clothing must be taken home, employers should ensure employees are thoroughly trained on the best practices to minimize or avoid non-work dust exposure (e.g., vacuum clothes before leaving the work area, wash work clothing separately, rinse washer before washing other household clothes, etc.).

Eye Protection:

Wear safety glasses with side shields or other forms of eye protection in compliance with appropriate OSHA standards to prevent eye irritation. The use of contact lenses is not recommended, unless used in conjunction with appropriate eye protection. Do not touch eyes with soiled body parts or materials. If possible, have eye-washing facilities readily available where eye irritation can occur.

9. PHYSICAL AND CHEMICAL PROPERTIES

ODOR AND APPEARANCE: White, odorless, fibrous material
CHEMICAL FAMILY: Vitreous Aluminosilicate Fibers
BOILING POINT: Not Applicable
WATER SOLUBILITY (%): Not Soluble in Water
MELTING POINT: 1760° C (3200° F)
SPECIFIC GRAVITY: 2.50 – 2.75
VAPOR PRESSURE: Not Applicable
pH: Not Applicable
VAPOR DENSITY (Air = 1): Not Applicable
% VOLATILE: Not Applicable
MOLECULAR FORMULA: Not Applicable

10. STABILITY AND REACTIVITY

CHEMICAL STABILITY: Stable under conditions of normal use.
INCOMPATIBILITY: Soluble in hydrofluoric acid, phosphoric acid, and concentrated alkali.
CONDITIONS TO AVOID: None.
HAZARDOUS DECOMPOSITION PRODUCTS: None.
HAZARDOUS POLYMERIZATION: Not Applicable.

11. TOXICOLOGICAL INFORMATION

HEALTH DATA SUMMARY

Epidemiological studies of RCF production workers have indicated no increased incidence of respiratory disease nor other significant health effects. In animal studies, long-term, high-dose inhalation exposure resulted in the development of respiratory disease in rats and hamsters.

EPIDEMIOLOGY

The University of Cincinnati is conducting an ongoing epidemiologic investigation. The evidence obtained from employees in U. S. RCF manufacturing facilities is as follows:

- 1) There is no evidence of any fibrotic lung disease (interstitial fibrosis) from evaluations of chest X-rays.
- 2) There is no evidence of an elevated incidence of lung disease among RCF manufacturing employees.

- 3) In early studies, an apparent statistical "trend" was observed, in the exposed population, between RCF exposure duration and some measures of lung function. The observations were clinically insignificant. If these observations were made on an individual employee, the results would be interpreted as being within the normal (predicted) respiratory range. A more recent longitudinal study of employees with 5 or more pulmonary function tests found that there was no effect on lung function associated with RCF production experience. Initial data (circa 1987) seemed to indicate an interactive effect between smoking and RCF exposure; more recent data, however, found no interactive effect. Nevertheless, to promote good health, RCF employees are still actively encouraged not to smoke.

- 4) Pleural plaques (thickening along the chest wall) have been observed in a small number of RCF employees. Some studies appear to show a relationship between the occurrence of pleural plaques on chest radiographs and the following variables: (a) date since RCF production hire date; (b) duration of RCF production employment; and (c) cumulative RCF exposure. The best evidence to date indicates that pleural plaques are a marker of exposure only. Pleural plaques are not associated with pulmonary impairment. The pathogenesis of pleural plaques remains incompletely understood; however, the mechanism appears to be an inflammatory response caused by inhaled fibers.

TOXICOLOGY

A number of toxicological studies designed to identify any potential health effects from RCF exposure have been completed. In one study, conducted by the Research and Consulting Company (Geneva, Switzerland), rats and hamsters were exposed to 30 mg/m³ (about 200 fibers/cc) of specially-prepared RCF for 6 hours/day, 5 days/week, for up to 24 months. In rats, a statistically significant increase in lung tumors was observed, two mesotheliomas (cancer of the pleural lining between the chest wall and lung) were also identified. Hamsters did not develop lung tumors, however, interstitial fibrosis and mesothelioma was found. Some, in the scientific community, have concluded that the "maximum tolerated dose" was exceeded and that significant particle contamination was a confounding issue; therefore, these study findings may not represent an accurate assessment of the potential for RCF to produce adverse health effects.

In a related multi-dose study with a similar protocol, other rats were exposed to doses of 16 mg/m³, 9 mg/m³, 3 mg/m³ which corresponds to about 115, 75, and 25 fibers per cubic centimeter respectively. This study found no statistically significant increase in lung cancer. Some cases of pleural and parenchymal fibrosis were seen in the 16 mg/m³ dose group. Some cases of mild fibrosis and one mesothelioma were observed in the 9 mg/m³ group. No acute respiratory effects were seen in the rats in the 3 mg/m³ exposure group, which suggests that there may be a dose/response threshold, below which irreversible respiratory impacts do not occur.

Other toxicological studies have been conducted which utilized non-physiological exposure methods such as intrapleural, intraperitoneal and intratracheal implantation or injection. Some of these studies have found that RCF is a potential carcinogen. Some experts, however, suggest that these tests have limited relevance because they bypass many of the biological mechanisms that prevent fiber deposition or facilitate fiber clearance.

To obtain more epidemiology or toxicology information, please call the toll free telephone number for the Unifrax Corporation Product Stewardship Program found in Section 16 - Other Information.

Chapter 12

12. ECOLOGICAL INFORMATION

No ecological concerns have been identified.

13. DISPOSAL CONSIDERATIONS

WASTE MANAGEMENT

To prevent waste materials from becoming airborne during waste storage, transportation and disposal, a covered container or plastic bagging is recommended.

DISPOSAL

RCF, as manufactured, is not classified as a hazardous waste according to Federal regulations (40 CFR 261). Any processing, use, alteration or chemical additions to the product, as purchased, may alter the disposal requirements. Under Federal regulations, it is the waste generator's responsibility to properly characterize a waste material, to determine if it is a "hazardous" waste. Check local, regional, state or provincial regulations to identify all applicable disposal requirements.

14. TRANSPORT INFORMATION

U.S. DEPARTMENT OF TRANSPORTATION (DOT)

Hazard Class:	Not Regulated	United Nations (UN) Number:	Not Applicable
Labels:	Not Applicable	North America (NA) Number:	Not Applicable
Placards:	Not Applicable	Bill of Lading:	Product Name

INTERNATIONAL

Canadian TDG Hazard Class & PIN: Not regulated
Not classified as dangerous goods under ADR (road), RID (train) or IMDG (ship).

INTERNATIONAL REGULATIONS

Canada:	Canadian Workplace Hazardous Materials Information System (WHMIS) – RCF is classified as Class D2A – Materials Causing Other Toxic Effects		
California:	Canadian Environmental Protection Act (CEPA) - All substances in this product are listed, as required, on the Domestic Substance List (DSL)		
Other States:	European Directive 97/69/EC classified RCF as a Category 2 carcinogen; that is it "should be regarded as if it is carcinogenic to man".		

16. OTHER INFORMATION

RCF DEVITRIFICATION

As produced, all RCF fibers are vitreous (glassy) materials which do not contain crystalline silica. Continued exposure to elevated temperatures may cause these fibers to devitrify (become crystalline). The first crystalline formation (mullite) begins to occur at approximately 985° C (1805° F). Crystalline phase silica may begin to form at temperatures of approximately 1200° C (2192° F). The occurrence and extent of crystalline phase formation is dependent on the duration and temperature of exposure, fiber chemistry and/or the presence of fluxing agents. The presence of crystalline phases can be confirmed only through laboratory analysis of the "hot face" fiber.

IARC's evaluation of crystalline silica states "Crystalline silica in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (Group 1)" and additionally notes "carcinogenicity in humans was not detected in all industrial circumstances studied" (IARC Monograph Vol. 68, 1997). NTP lists all polymorphs of crystalline silica amongst substances which may "reasonably be anticipated to be carcinogens".

15. REGULATORY INFORMATION

UNITED STATES REGULATIONS

Appendix - MSDS

injection; and (2) after-service RCF was not cytotoxic to macrophage-like cells at concentrations up to 320 g/cm² - by comparison, pure quartz or cristobalite were significantly active at much lower levels (circa 20 g/cm²).

RCF AFTER-SERVICE REMOVAL

Respiratory protection should be provided in compliance with OSHA standards. During removal operations, a full face respirator is recommended to reduce inhalation exposure along with eye and respiratory tract irritation. A specific evaluation of workplace hazards and the identification of appropriate respiratory protection is best performed, on a case by case basis, by a qualified industrial hygiene professional.

PRODUCT STEWARDSHIP PROGRAM

The Unifrax Corporation has established a program to provide customers with up-to-date information regarding the proper use and handling of refractory ceramic fiber. In addition, Unifrax Corporation has also established a program to monitor airborne fiber concentrations at customer facilities. If you would like more information about this program, please call the Unifrax Corporation Product Stewardship Information Hotline at 1-800-322-2293.

On February 11, 2002, the Refractory Ceramic Fiber's Coalition (RCFC) and the U.S. Occupational Safety and Health Administration (OSHA) introduced a voluntary worker protection program entitled PSP 2002, a comprehensive, multi-faceted risk management program designed to control and reduce workplace exposures to refractory ceramic fiber (RCF). Unifrax Corporation, as a member of RCFC, is participating in this highly acclaimed product stewardship program. For more information regarding PSP 2002, please call the Unifrax Corporation's Product Stewardship Information Hotline at 1-800-322-2293 or refer to the RCFC web site: <http://www.rcfc.net>.

NIOSH:	National Institute for Occupational Safety and Health
OSHA:	Occupational Safety and Health Administration
29 CFR 1910.134 &	OSHA Respiratory Protection Standards
29 CFR 1910.103;	
29 CFR 1910.1200 &	OSHA Hazard Communication Standards
1926.59:	Permissible Exposure Limit (OSHA)
PEL:	Product Identification Number
PIN:	Particulates Not Otherwise Classified
PNOC:	Particulates Not Otherwise Regulated
PNOR:	Product Stewardship Program
PSP:	Refractory Ceramic Fibers Coalition
RCFC:	Resource Conservation and Recovery Act
RCRA:	Recommended Exposure Guideline (RCFC)
REG:	Carnage of Dangerous Goods by Rail (International Regulations)
REL:	Superfund Amendments and Reauthorization Act
RID:	Emergency Planning and Community Right to Know Act
SARA:	Extremely Hazardous Substances
SARA Title III:	MSDS/List of Chemicals and Hazardous Inventory
SARA Section 302:	Emergency and Hazardous Inventory
SARA Section 304:	Toxic Chemicals and Release Reporting
SARA Section 311:	Short Term Exposure Limit ¹
SARA Section 312:	Synthetic Vitreous Fiber
SARA Section 313:	Transportation of Dangerous Goods
STEL:	Threshold Limit Value (ACGIH)
SVF:	Toxic Substances Control Act
TDG:	Time Weighted Average
TLV:	TSCA:
TWA:	Workplace Hazardous Materials Information System (Canada)
WHMIS:	

Revision Summary: Minor modification to devitrification section. Replaces 06/10/03 MSDS

MSDS Prepared By: UNIFRAX RISK MANAGEMENT DEPARTMENT

DEFINITIONS

ACGIH:	American Conference of Governmental Industrial Hygienists
ADR:	Carnage of Dangerous Goods by Road (International Regulation)
CAA:	Clean Air Act
CAS:	Chemical Abstracts Service
CERCLA:	Comprehensive Environmental Response, Compensation and Liability Act
DSL:	Domestic Substances List
EPA:	Environmental Protection Agency
EU:	European Union
f/c:	Fibers per cubic centimeter
HEPA:	High Efficiency Particulate Air
HMIS:	Hazardous Materials Identification System
IARC:	International Agency for Research on Cancer
ITATE:	International Maritime Dangerous Goods Code
IMDG:	International Air Transport Association
m/m ³ :	Milligrams per cubic meter of air
mm ³ /cf:	Million particles per cubic meter
NFPA:	National Fire Protection Association

DISCLAIMER
The information presented herein is presented in good faith and believed to be accurate as of the effective date of this Material Safety Data Sheet. Employers may use this MSDS to supplement other information gathered by them in their efforts to assure the health and safety of their employees and the proper use of the product. This summary of the relevant data reflects professional judgment; employers should note that information perceived to be less relevant has not been included in this MSDS. Therefore, given the summary nature of this document, Unifrax Corporation does not extend any warranty (expressed or implied), assume any responsibility, or make any representation regarding the completeness of this information or its suitability for the purposes envisioned by the user.

12.4 MSDS M0055 Fiberfrax® High Purity Papers

OTHER POTENTIAL EFFECTS	
TARGET ORGANS:	Respiratory Tract (nose & throat), Eyes, Skin
RESPIRATORY TRACT (nose & throat) IRRITATION:	If inhaled in sufficient quantity, may cause temporary, mild mechanical irritation to respiratory tract. Symptoms may include scratchiness of the nose or throat, cough or chest discomfort.
EYE IRRITATION:	May cause temporary, mild mechanical irritation. Fibers may be abrasive; prolonged contact may cause damage to the outer surface of the eye.
SKIN IRRITATION:	May cause temporary, mild mechanical irritation. Exposure may also result in inflammation, rash or itching.
GASTROINTESTINAL IRRITATION:	Unlikely route of exposure.
MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:	Pre-existing medical conditions, including dermatitis, asthma or chronic lung disease may be aggravated by exposure; individuals who have a history of allergies may experience greater amounts of skin and respiratory irritation.
HAZARD CLASSIFICATION	Although studies, involving occupationally exposed workers, have not identified any increased incidence of respiratory disease, results from animal testing have been used as the basis for hazard classification. In each of the following cases, the conclusions are qualitative only and do not rest upon any quantitative analysis suggesting that the hazard actually may occur at current occupational exposure levels.
	In October 2001, the International Agency for Research on Cancer (IARC) confirmed that Group 2b (possible human carcinogen) remains the appropriate IARC classification for RCF.
	The Seventh Annual Report on Carcinogens (1994), prepared by the National Toxicology Program (NTP), classified respirable RCF and glasswool as substances reasonably anticipated to be carcinogens.
	The American Conference of Governmental Industrial Hygienists (ACGIH) has classified RCF as "A2-Suspected Human Carcinogen".
	The Commission of The European Communities (DG XI) has classified RCF as a substance that should be regarded as if it is carcinogenic to man.

MATERIAL SAFETY DATA SHEET	
MSDS No. M0055	Effective Date: 03/09/2004
1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION	
Product Group:	REFRACTORY CERAMIC FIBER PRODUCT
Chemical Name:	VITREOUS ALUMINOSILICATE FIBER
Synonym(s):	RCF, ceramic fiber, synthetic vitreous fiber (SVF), man-made vitreous fiber (MMVF), man-made mineral fiber (MMMF)
Trade Names:	FIBERFRAX® HIGH PURITY PAPERS 550-F, 550-J, 550-K, 880-F, 880-J, 970-F, 970-J, 970-K, Rollboard, HSA-F with binder, HSA-J with binder, QSP100, QSP300, QSP500, QSP1000.
Manufacturer/Supplier:	Unifrax Corporation 2351 Whirlpool St. Niagara Falls, NY 14305-2413
Product Stewardship Information Hotline	1-800-322-2293 (Monday - Friday 8:00 a.m. - 4:30 p.m. EST)
For additional MSDSs, visit our web page, http://www.unifrax.com , or call Unifrax Customer Service at (716) 278-3872	
CHEMTREC Assist:	CHEMTREC will provide assistance for chemical emergencies. Call 1-800-424-9300
2. COMPOSITION / INFORMATION ON INGREDIENTS	
COMPONENTS	% BY WEIGHT
Refractories, Fibers, Aluminosilicate	85-95
Acrylic latex	5-15
(See Section 8 "Exposure Controls / Personal Protection" for exposure guidelines)	
3. HAZARDS IDENTIFICATION	
EMERGENCY OVERVIEW	
WARNING!	POSSIBLE CANCER HAZARD BY INHALATION. (See Section 11 for more information)
CHRONIC EFFECT	
There has been no increased incidence of respiratory disease in studies examining occupationally exposed workers. In animal studies, long-term laboratory exposure to doses hundreds of times higher than normal occupational exposures has produced fibrosis, lung cancer, and mesothelioma in rats or hamsters. The fibers used in those studies were specially sized to maximize rodent respirability.	

Appendix - MSDS

The State of California, pursuant to Proposition 65, The Safe Drinking Water and Toxic Enforcement Act of 1986, has listed "ceramic fibers (airborne fibers of respirable size)" as a chemical known to the State of California to cause cancer.

The Canadian Environmental Protection Agency (CEPA) has classified RCF as "probably carcinogenic" (Group 2).

The Canadian Workplace Hazardous Materials Information System (WHMIS) – RCF is classified as Class D2A – Materials Causing Other Toxic Effects

The Hazardous Materials Identification System (HMIS) –

Health 1*	Flammability 0	Reactivity 0	Personal Protection Index: X (Employer Determined)
-----------	----------------	--------------	--

(* denotes potential for chronic effects)

Skin and respiratory effects are the result of temporary, mild mechanical irritation; fiber exposure does not result in allergic manifestations.

5. FIRE FIGHTING MEASURES

NFPA Codes: Flammability: 0 Health: 1 Reactivity: 0 Special: 0

NFPA Unusual Hazards: None
Flammable Properties: None
Flash Point: None
Hazardous Decomposition Products: Thermal decomposition of binder from fires or from first heat of product may release smoke, carbon monoxide, carbon dioxide, oxides of nitrogen and small amounts of aromatic and aliphatic hydrocarbons. Use adequate ventilation or other precautions to eliminate exposure to vapors resulting from thermal decomposition of binder. Exposure to thermal decomposition fumes may cause respiratory tract irritation, bronchial hyper-reactivity or an asthmatic-type response.
Unusual Fire and Explosion Hazard: None
Extinguishing Media: Use extinguishing media suitable for type of surrounding fire.

6. ACCIDENTAL RELEASE MEASURES

SPILL PROCEDURES

Avoid creating airborne dust. Dust suppressing cleaning methods such as wet sweeping or vacuuming should be used to clean the work area. If vacuuming, the vacuum must be equipped with a HEPA filter. Compressed air or dry sweeping should not be used for cleaning.

4. FIRST AID MEASURES

FIRST AID PROCEDURES

RESPIRATORY TRACT (nose & throat) IRRITATION:

If respiratory tract irritation develops, move the person to a dust free location. Get medical attention if the irritation continues. See Section 8 for additional measures to reduce or eliminate exposure.

EYE IRRITATION:
If eyes become irritated, flush immediately with large amounts of lukewarm water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Do not rub eyes. Get medical attention if irritation persists.

SKIN IRRITATION:
If skin becomes irritated, remove soiled clothing. Do not rub or scratch exposed skin. Wash area of contact thoroughly with soap and water. Using a skin cream or lotion after washing may be helpful.

GASTROINTESTINAL IRRITATION:
If gastrointestinal tract irritation develops, move the person to a dust free environment.

NOTES TO PHYSICIANS:

7. HANDLING AND STORAGE

STORAGE

Store in original container in a dry area. Keep container closed when not in use.

HANDLING

Handle ceramic fiber carefully. Limit use of power tools unless in conjunction with local exhaust. Use hand tools whenever possible. Frequently clean the work area with HEPA filtered vacuum or wet sweeping to minimize the accumulation of debris. Do not use compressed air for clean-up.

EMPTY CONTAINERS

Product packaging may contain residue. Do not reuse.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE GUIDELINES -- RCF

COMPONENTS

OSHA PEL

MANUFACTURER REG

Chapter 12

concentrations within the 0.5 f/cc REG, the use of appropriate respiratory protection, pursuant to the requirements of OSHA Standards 29 CFR 1910.134 and 29 CFR 1926.103, is recommended.

The following information is provided as an example of appropriate respiratory protection for aluminosilicate fibers. The evaluation of workplace hazards and the identification of appropriate respiratory protection is best performed, on a case by case basis, by a qualified Industrial Hygienist.

Refractories, Fibers, Aluminosilicate	None Established*	0.5 f/cc, 8-hr. TWA**
--	-------------------	-----------------------

* There is no specific regulatory standard for RCF in the U.S. OSHA's "Particulate Not Otherwise Regulated (PNOR)" standard [29 CFR 1910.1000, Subpart Z, Air Contaminants] applies generally; Total Dust 15 mg/m³; Respirable Fraction 5 mg/m³.

** The Refractory Ceramic Fibers Coalition (RCFC) has sponsored comprehensive toxicology epidemiology studies to identify potential RCF-related health effects (see Section 11 for more details), consulted experts familiar with fiber and particle science, conducted a thorough review of the RCF-related scientific literature, and further evaluated the data in a state-of-the-art quantitative risk assessment. Based on these efforts and in the absence of an OSHA PEL, RTI has adopted a recommended exposure guideline, as measured under NIOSH Method 7400 [The manufacturers' REG is intended to promote occupational health and safety through prudent exposure control and reduction and it reflects relative technical and economic feasibility as determined by extensive industrial hygiene monitoring efforts undertaken pursuant to an agreement with the U.S. Environmental Protection Agency].

OTHER OCCUPATIONAL EXPOSURE LEVELS (OEL)

RCF-related occupational exposure limits vary internationally. Regulatory OEL examples include Australia – 0.5 f/cc; Austria – 0.5 f/cc; Canada – 0.5 to 1.0 f/cc; Denmark – 1.0 f/cc; France – 0.5 f/cc; Germany – 0.5 f/cc; Netherlands – 1.0 f/cc; New Zealand – 1.0 f/cc; Norway – 1.0 f/cc; Poland – 2.0 f/cc; Sweden – 1.0 f/cc; United Kingdom – 2.0 f/cc. Non-regulatory OEL examples include: ACGIH TLV 0.2 f/cc; RCFC REG 0.5 f/cc. The objectives and criteria underlying each of these OEL decisions also vary. The evaluation of occupational exposure limits and determining their relative applicability to the workplace is best performed, on a case-by-case basis, by a qualified Industrial Hygienist.

EXPOSURE GUIDELINES – OTHER INGREDIENTS

COMPONENTS	OSHA PEL	MANUFACTURER REG
Acrylic latex	None established	None established

OTHER OCCUPATIONAL EXPOSURE LEVELS (OEL)

Non-regulatory OEL examples include: ACGIH TLVs (TWA): Acrylic latex – None established

ENGINEERING CONTROLS

Use engineering controls such as local exhaust ventilation, point of generation dust collection down draft work stations, emission controlling tool designs, and materials handling equipment designed to minimize airborne fiber emissions.

- PERSONAL PROTECTION EQUIPMENT
- Respiratory Protection – RCF:

When engineering and/or administrative controls are insufficient to maintain workplace

MANUFACTURER'S RESPIRATORY PROTECTION RECOMMENDATIONS WHEN HANDLING RCF PRODUCTS	
Respirable Airborne Fiber Concentration (levels are 8-hr. time-weighted averages)	Respirator Recommendation [†]
Not yet determined but expected to be below 5.0 f/cc based on operation	Half-face, air purifying respirator equipped with a NIOSH certified P100 particulate filter cartridge
"Reliably" less than 0.5 f/cc	Optional
0.5 f/cc to 5.0 f/cc	Half-face, air purifying respirator equipped with a NIOSH certified P100 particulate filter cartridge
5.0 f/cc to 25 f/cc	Full-facepiece, air purifying respirator equipped with a NIOSH certified P100 particulate filter cartridge or PAPR
Greater than 25 f/cc	PAPR with tight-fitting full facepiece or a supplied air respirator in continuous flow mode
When individual workers request respiratory protection as a matter of personal comfort or choice where exposures are "reliably" below 0.5 f/cc	A NIOSH certified respirator, such as a disposable particulate respirator, or respirators with filter cartridges rated N95 or better

- [†]The P100 recommendation is a conservative default choice; in some case, solid arguments can be made that other respirator types (e.g., N95, R99, etc.) may be suitable for some tasks or work environments. The P100 recommendation is not designed to limit informed choices, provided that respiratory protection decisions comply with 29 CFR 1910.134.
- Other Information:
 - Concentrations based upon an eight-hour time weighted average (TWA) as determined by air samples collected and analyzed pursuant to NIOSH method 7400 (B) for airborne fibers.
 - The manufacturer recommends the use of a full-facepiece air purifying respirator equipped with an appropriate particulate filter cartridge during furnace tear-out events and the removal of used RCF to control exposures to airborne fiber and the potential presence of crystalline silica. If exposure levels are known, the respiratory protection chart provided above may be applied.
 - Potential exposure to other airborne contaminants should be evaluated by a qualified Industrial Hygienist for the selection of appropriate respiratory protection and air monitoring.

Appendix - MSDS

Skin Protection:

Wear gloves, head coverings and full body clothing as necessary to prevent skin irritation. Washable or disposable clothing may be used. If possible, do not take unwashed clothing home. If soiled work clothing must be taken home, employers should ensure employees are thoroughly trained on the best practices to minimize or avoid non-work dust exposure (e.g., vacuum clothes before leaving the work area, wash work clothing separately, rinse washer before washing other household clothes, etc.).

Eye Protection:

Wear safety glasses with side shields or other forms of eye protection in compliance with appropriate OSHA standards to prevent eye irritation. The use of contact lenses is not recommended, unless used in conjunction with appropriate eye protection. Do not touch eyes with soiled body parts or materials. If possible, have eye-washing facilities readily available where eye irritation can occur.

HEALTH DATA SUMMARY

Epidemiological studies of RCF production workers have indicated no increased incidence of respiratory disease nor other significant health effects. In animal studies, long-term, high-dose inhalation exposure resulted in the development of respiratory disease in rats and hamsters.

EPIDEMOLOGY

The University of Cincinnati is conducting an ongoing epidemiologic investigation. The evidence obtained from employees in U. S. RCF manufacturing facilities is as follows:

- 1) There is no evidence of any fibrotic lung disease (interstitial fibrosis) from evaluations of chest X-rays.
- 2) There is no evidence of an elevated incidence of lung disease among RCF manufacturing employees.

9. PHYSICAL AND CHEMICAL PROPERTIES

ODOR AND APPEARANCE	White, odorless, fibrous material
CHEMICAL FAMILY	Vitreous Aluminosilicate Fibers
BODING POINT	Not Applicable
WATER SOLUBILITY (%)	Not Soluble in Water
MELTING POINT	1760° C (3200° F)
SPECIFIC GRAVITY	2.50 – 2.75
VAPOR PRESSURE	Not Applicable
pH	Not Applicable
VAPOR DENSITY (Air = 1):	Not Applicable
% VOLATILE	Not Applicable
MOLECULAR FORMULA:	Not Applicable

10. STABILITY AND REACTIVITY

Stable under conditions of normal use. Soluble in hydrofluoric acid, phosphoric acid, and concentrated alkali.

None.

Thermal decomposition of binder from fires or from first heat of product may release smoke, carbon monoxide, carbon dioxide, oxides of nitrogen and small amounts of aromatic and aliphatic hydrocarbons. Use adequate ventilation or other precautions to eliminate exposure to vapors resulting from thermal decomposition of binder. Exposure to thermal decomposition fumes may cause respiratory tract irritation, bronchial hyper-reactivity or an asthmatic-type response.

Not Applicable.

CHEMICAL STABILITY:
INCOMPATIBILITY:
CONDITIONS TO AVOID:
HAZARDOUS DECOMPOSITION PRODUCTS:

A number of toxicological studies designed to identify any potential health effects from RCF exposure have been completed. In one study, conducted by the Research and Consulting Company, (Geneva, Switzerland), rats and hamsters were exposed to 30 mg/m³ (about 200 fibers/cc) of specially prepared RCF for 6 hours/day, 5 days/week, for up to 24 months. In rats, a statistically significant increase in lung tumors was observed; two mesotheliomas (cancer of the pleural lining between the chest wall and lung) were also identified. Hamsters did not develop lung tumors; however, interstitial fibrosis and mesothelioma was found. Some in the scientific community, have concluded that the "maximum tolerated dose" was exceeded and that significant particle contamination was a confounding issue; therefore, these study findings may not represent an accurate assessment of the potential for RCF to produce adverse health effects.

In a related multi-dose study with a similar protocol, other rats were exposed to doses of 16 mg/m³, 9 mg/m³, 3 mg/m³ which corresponds to about 115, 75, and 25 fibers per cubic centimeter respectively. This study found no statistically significant increase in lung cancer. Some cases of pleural and parenchymal fibrosis were seen in the 16 mg/m³ dose group. Some cases of mild

Chapter 12

15. REGULATORY INFORMATION

fibrosis and one mesothelioma were observed in the 9 mg/m³ group. No acute respiratory effects were seen in the rats in the 3 mg/m³ exposure group, which suggests that there may be a dose/response threshold, below which irreversible respiratory impacts do not occur.

Other toxicological studies have been conducted which utilized non-physiological exposure methods such as intrapleural, intraperitoneal and intratracheal implantation or injection. Some of these studies have found that RCF is a potential carcinogen. Some experts, however, suggest that these tests have limited relevance because they bypass many of the biological mechanisms that prevent fiber deposition or facilitate fiber clearance.

To obtain more epidemiology or toxicology information, please call the toll free telephone number for the Unifrax Corporation Product Stewardship Program found in Section 16 - Other Information.

12. ECOLOGICAL INFORMATION

No ecological concerns have been identified.

13. DISPOSAL CONSIDERATIONS

WASTE MANAGEMENT

To prevent waste materials from becoming airborne during waste storage, transportation and disposal, a covered container or plastic bagging is recommended.

DISPOSAL

RCF, as manufactured, is not classified as a hazardous waste according to Federal regulations (40 CFR 261). Any processing, use, alteration or chemical additions to the product, as purchased, may alter the disposal requirements. Under Federal regulations, it is the waste generator's responsibility to properly characterize a waste material, to determine if it is a "hazardous" waste. Check local, regional, state or provincial regulations to identify all applicable disposal requirements.

14. TRANSPORT INFORMATION

U.S. DEPARTMENT OF TRANSPORTATION (DOT)

Hazard Class:	Not Regulated	United Nations (UN) Number:	Not Applicable
Labels:	Not Applicable	North America (NA) Number:	Not Applicable
Placards:	Not Applicable	Bill of Lading:	Product Name

INTERNATIONAL

Canadian TDG Hazard Class & PIN: Not regulated
Not classified as dangerous goods under ADR (road), RID (train) or IMDG (ship).

UNITED STATES REGULATIONS

EPA:	Superfund Amendments and Reauthorization Act (SARA) Title III - This product does not contain any substances reportable under Sections 302, 304, 313, (40 CFR 372). Sections 311 and 312 (40 CFR 370) apply (delayed hazard).
Toxic Substances Control Act (TSCA) - All substances in this product are listed, as required, on the TSCA inventory. RCF has been assigned a CAS number; however, it is a simple mixture and therefore not required to be listed on the TSCA inventory. The components of RCF are listed on the inventory.	Comprehensive Environmental Response, Compensation and Liability Act (CERCLA) and the Clean Air Act (CAA) - RCF contains fibers with an average diameter greater than one micron and thus is not considered a hazardous air pollutant.
OSHA:	Comply with Hazard Communication Standards 29 CFR 1910.1200 and 29 CFR 1926.59 and the Respiratory Protection Standards 29 CFR 1910.134 and 29 CFR 1926.103.
California:	Ceramic fibers (airborne particles of respirable size) is listed in Proposition 65, The Safe Drinking Water and Toxic Enforcement Act of 1986 as a chemical known to the State of California to cause cancer.
Other States:	RCF products are not known to be regulated by states other than California; however, state and local OSHA and EPA regulations may apply to these products. If in doubt, contact your local regulatory agency.

INTERNATIONAL REGULATIONS

Canada:

Canadian Workplace Hazardous Materials Information System (WHMIS) – RCF is classified as Class D2A – Materials Causing Other Toxic Effects Canadian Environmental Protection Act (CEPA) - All substances in this product are listed, as required, on the Domestic Substance List (DSL) European Directive 97/69/EC classified RCF as a Category 2 carcinogen; that is it "should be regarded as if it is carcinogenic to man."

16. OTHER INFORMATION

RCF DEVITRIFICATION

As produced, all RCF fibers are vitreous (glassy) materials which do not contain crystalline silica. Continued exposure to elevated temperatures may cause these fibers to devitrify (become crystalline). The first crystalline formation (mullite) begins to occur at approximately 955° C (1805° F). Crystalline phase silica may begin to form at temperatures of approximately 1200° C (2192° F). The occurrence and extent of crystalline phase formation is dependent on the duration and temperature of exposure, fiber chemistry and/or the presence of fluxing agents. The presence of crystalline phases can be confirmed only through laboratory analysis of the "hot face" fiber.

IARC's evaluation of crystalline silica states "Crystalline silica inhaled in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (Group 1)" and additionally notes "carcinogenicity in humans was not detected in all industrial circumstances studied" (IARC Monograph Vol. 68, 1997). NTP lists all polymorphs of crystalline silica among substances which may "reasonably be anticipated to be carcinogens".

Appendix - MSDS

IARC and NTP did not evaluate after-service RCF, which may contain various crystalline phases. However, an analysis of after-service RCF samples obtained pursuant to an exposure monitoring agreement with the USEPA, found that in the furnace conditions sampled, most did not contain detectable levels of crystalline silica. Other relevant RCF studies found that: (1) simulated after-service RCF showed little, or no, activity where exposure was by inhalation or by intraperitoneal injection; and (2), after-service RCF was not cytotoxic to macrophage-like cells at concentrations up to 320 g/cm² - by comparison, pure quartz or cristobalite were significantly active at much lower levels (circa 20 g/cm²).

RCF AFTER-SERVICE REMOVAL

Respiratory protection should be provided in compliance with OSHA standards. During removal operations, a full face respirator is recommended to reduce inhalation exposure along with eye and respiratory tract irritation. A specific evaluation of workplace hazards and the identification of appropriate respiratory protection is best performed, on a case by case basis, by a qualified industrial hygiene professional.

PRODUCT STEWARDSHIP PROGRAM

The Unifrax Corporation has established a program to provide customers with up-to-date information regarding the proper use and handling of refractory ceramic fiber. In addition, Unifrax Corporation has also established a program to monitor airborne fiber concentrations at customer facilities. If you would like more information about this program, please call the Unifrax Corporation Product Stewardship Information Hotline at 1-800-322-2293.

On February 11, 2002, the Refractory Ceramic Fibers Coalition (RCFC) and the U.S. Occupational Safety and Health Administration (OSHA) introduced a voluntary worker protection program entitled PSP 2002, a comprehensive, multi-faceted risk management program designed to control and reduce workplace exposures to refractory ceramic fiber (RCF). Unifrax Corporation, as a member of RCFC, is participating in this highly acclaimed product stewardship program. For more information regarding PSP 2002, please call the Unifrax Corporation's Product Stewardship Information Hotline at 1-800-322-2293 or refer to the RCFC web site: <http://www.rcfc.net>.

DEFINITIONS

ACGIH:	American Conference of Governmental Industrial Hygienists
ADR:	Carriage of Dangerous Goods by Road (International Regulation)
CAA:	Clean Air Act
CAS:	Chemical Abstracts Service
CERCLA:	Comprehensive Environmental Response, Compensation and Liability Act
DSL:	Domestic Substances List
EPA:	Environmental Protection Agency
EU:	European Union
fcc:	Fibers per cubic centimeter
HEPA:	High Efficiency Particulate Air
HMIS:	Hazardous Materials Identification System
IARC:	International Agency for Research on Cancer
ATA:	International Air Transport Association
IMDG:	International Maritime Dangerous Goods Code
mg/m ³ :	Milligrams per cubic meter of air
mmpcf:	Million particles per cubic meter
NFPA:	National Fire Protection Association

National Institute for Occupational Safety and Health
Occupational Safety and Health Administration
OSHA Respiratory Protection Standards
29 CFR 1910.134 &
1926.103;
29 CFR 1910.1200 &
1926.59;
PEL:
PIN:
PNOC:
PNOR:
PSP:
RCFC:
RCRA:
REG:
REL:
RID:
SARA:
SARA Title III:
SARA Section 302:
SARA Section 304:
SARA Section 311:
SARA Section 312:
SARA Section 313:
STEL:
SVF:
TDG:
TLV:
TSCA:
TWA:
WHMIS:

Permissible Exposure Limit (OSHA)
Product Identification Number
Particulates Not Otherwise Classified
Particulates Not Otherwise Regulated
Product Stewardship Program
Refractory Ceramic Fibers Coalition
Resource Conservation and Recovery Act
Recommended Exposure Guideline (RCFC)
Recommended Exposure Limit (NIOSH)
Carriage of Dangerous Goods by Rail (International Regulations)
Superfund Amendments and Reauthorization Act
Emergency Planning and Community Right to Know Act
Extremely Hazardous Substances
Emergency Release
MSDS/List of Chemicals and Hazardous Inventory
Emergency and Hazardous Inventory
Toxic Chemicals and Release Reporting
Short Term Exposure Limit
Synthetic Vitreous Fiber
Transportation of Dangerous Goods
Threshold Limit Value (ACGIH)
Toxic Substances Control Act
Time Weighted Average
Workplace Hazardous Materials Information System (Canada)
Revision Summary: Minor modification to devitification section. Replaces 2/11/02 MSDS.

MSDS Prepared By: UNIFRAX RISK MANAGEMENT DEPARTMENT

DISCLAIMER

The information presented herein is presented in good faith and believed to be accurate as of the effective date of this Material Safety Data Sheet. Employers may use this MSDS to supplement other information gathered by them in their efforts to assure the health and safety of their employees and the proper use of the product. This summary of the relevant data reflects professional judgment; employers should note that information perceived to be less relevant has not been included in this MSDS. Therefore, given the summary nature of this document, Unifrax Corporation does not extend any warranty (expressed or implied), assume any responsibility, or make any representation regarding the completeness of this information or its suitability for the purposes envisioned by the user.

Chapter 12

12.5 Kaowool® Insulation MSDS 203

MSDS No:	203	Date Prepared:	08/01/1987	Current Date:	4/13/2006
			Last Revised: (04/13/2006)		
<p>CHRONIC EFFECT There has been no increased incidence of respiratory disease in studies examining occupationally exposed workers. In animal studies, long term laboratory exposure to doses hundreds of times higher than normal occupational exposures has produced fibrosis, lung cancer and mesothelioma in rats or hamsters. The fibers used in those studies were specially sized to maximize rodent respirability.</p>					
<p>TARGET ORGANS: Respiratory Tract (nose and throat), Eyes, Skin</p>					
<p>RESPIRATORY TRACT (nose and throat) IRRITATION: If inhaled in sufficient quantity, may cause temporary, mild mechanical irritation to respiratory tract. Symptoms may include scratchiness of the nose or throat, cough or chest discomfort.</p>					
<p>EYE IRRITATION: May cause temporary, mild mechanical irritation. Fibers may be abrasive; prolonged contact may cause damage to the outer surface of the eye.</p>					
<p>SKIN IRRITATION: May cause temporary, mild mechanical irritation. Exposure may also result in inflammation, rash or itching.</p>					
<p>GASTROINTESTINAL IRRITATION: Unlikely route of exposure.</p>					
<p>MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Pre-existing medical conditions, including dermatitis, asthma or chronic lung disease may be aggravated by exposure; individuals who have a history of allergies may experience greater amounts of skin and respiratory irritation.</p>					
<p>HAZARD CLASSIFICATION Although studies, involving occupationally exposed workers, have not identified any increased incidence of respiratory disease, results from animal testing have been used as the basis for hazard classification. In each of the following cases, the conclusions are qualitative only and do not rest upon any quantitative analysis suggesting that the hazard actually may occur at current occupational exposure levels.</p>					
<p>The International Agency for Research on Cancer (IARC) confirmed in October 2001 that Group 2B (possibly human carcinogen based on sufficient evidence of carcinogenicity in animals but inadequate evidence in humans) continues to be the appropriate classification for refractory ceramic fiber.</p>					
<p>The Seventh Annual Report on Carcinogens (1994), prepared by the National Toxicology Program (NTP), classified respirable RCF and glasswool as substances reasonably anticipated to be carcinogens.</p>					
<p>The American Conference of Governmental Industrial Hygienists (ACGIH) has classified RCF as "A2-Suspected Human Carcinogen."</p>					
<p>The Commission of The European Communities (DG XI) has classified RCF as a substance "that should be regarded as if it is carcinogenic to man."</p>					
<p>The State of California, pursuant to Proposition 65, "The Safe Drinking Water and Toxic Enforcement Act of 1986" has listed "ceramic fibers (airborne fibers of respirable size)" as a chemical known to the State of California to cause cancer.</p>					
<p>The Canadian Environmental Protection Agency (CEPA) has classified RCF as "probable carcinogenic" (Group 2).</p>					
<p>The Canadian Workplace Hazardous Materials Information System (WHMIS) - RCF is classified as Class D2A - Materials Causing Other Toxic Effects.</p>					
<p>The Hazardous Materials Identification System (HMIS) - Health 1* Flammability 0 Reactivity 0 (* denotes potential for chronic effects)</p>					
<p>Personal Protection Index: X (Employer Determined)</p>					

<p>Thermal Ceramics</p>					
<p>MATERIAL SAFETY DATA SHEET</p>					
MSDS No:	203	Date Prepared:	08/01/1987	Current Date:	4/13/2006
			Last Revised: (04/13/2006)		
<p>1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION</p>					
<p>Product Group: REFRactory CERAMIC FIBER PRODUCT Chemical Name: VITREOUS ALUMINOSILICATE FIBER Synonyms: RCF, ceramic fiber, synthetic vitreous fiber (SVF), man-made mineral fiber (MMMF), man-made vitreous fiber (MMVF), man-made mineral fiber (MMMF) Trade Names: PADSEALTS(WRAPPS) KaoWool® Wet (all grades) KaoWool® Element Support KaoWool® RIS-A Ceramite® Wet Wrap HT Pyro-Bloc® Plus XT Pyro-Bloc® Plus IT BOARDS and SHAPES KaoWool® 12C, M, Rigidized M, HP, PM, HT, 2300R, 2300H, VIF, 399E Cerafom® 102, 103, 140, 141, Custom Molded FireMaster® FireMaster® NS TM 2300 Thermatec® HT, HP, LD, A, AR Thermal Ceramics Inc. P.O. Box 923; Dept. 300 Augusta, GA 30903-0923 For Product Stewardship and Emergency Information - Hotline: 1-800-772-5681 Fax: 706-560-4054</p>					
<p>For additional MSDS and to confirm this is the most current MSDS for the product, visit our web page [www.thermalceramics.com].</p>					
<p>2. COMPOSITION / INFORMATION ON INGREDIENTS</p>					
COMPONENTS	GAS NUMBER	% BY WEIGHT			
Refractories, Fibers, Aluminosilicate	142844-00-0	65 - 90			
Silica, amorphous	7631-96-0	5 - 15			
Starch	9005-25-8	4 - 8			
<p>(See Section 8 "Exposure Controls / Personal Protection" for exposure guidelines)</p>					
<p>3. HAZARDS IDENTIFICATION</p>					
<p>EMERGENCY OVERVIEW</p>					
<p>WARNING! POSSIBLE CANCER HAZARD BY INHALATION.</p>					
<p>(See Section 11 for more information)</p>					

Appendix - MSDS

<p>MSDS No: 203 Date Prepared: 08/01/1987 Current Date: 4/13/2006 Last Revised: (04/13/2006)</p>	<p>MSDS No: 203 Date Prepared: 08/01/1987 Current Date: 4/13/2006 Last Revised: (04/13/2006)</p>																					
4. FIRST AID MEASURES																						
<p>RESPIRATORY TRACT (nose and throat) IRRITATION: If respiratory tract irritation develops, move the person to a dust free location. See Section 8 for additional measures to reduce or eliminate exposure.</p> <p>EYE IRRITATION: If eyes become irritated, flush immediately with large amounts of lukewarm water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Do not rub eyes.</p> <p>SKIN IRRITATION: If skin becomes irritated, remove soiled clothing. Do not rub or scratch exposed skin. Wash area of contact thoroughly with soap and water. Using a skin cream or lotion after washing may be helpful.</p> <p>GASTROINTESTINAL IRRITATION: If gastrointestinal tract irritation develops, move the person to a dust free environment.</p> <p style="text-align: center;">- If the above symptoms persist, seek medical attention. -</p>																						
<p>NOTES TO PHYSICIANS: Skin and respiratory effects are the result of temporary, mild mechanical irritation; fiber exposure does not result in allergic manifestations.</p>																						
5. FIRE FIGHTING MEASURES																						
<p>NFPA Codes: Flammability: 0 Health: 1 Reactivity: 0 Special: 0</p> <p>NFPA Unusual Hazards: None</p> <p>Flammable Properties: None</p> <p>Flash Point: None</p> <p>Hazardous Decomposition Products: None</p> <p>Unusual Fire and Explosion Hazard: None</p> <p>Extinguishing Media: Use extinguishing media suitable for type of surrounding fire</p>																						
6. ACCIDENTAL RELEASE MEASURES																						
<p>SPILL PROCEDURES: Avoid creating airborne dust. Dust suppressing cleaning methods such as wet sweeping or vacuuming should be used to clean the work area. If vacuuming, the vacuum should be equipped with a HEPA filter. Compressed air or dry sweeping should not be used for cleaning.</p>																						
7. HANDLING AND STORAGE																						
<p>HANDLING: Handle ceramic fiber carefully. Limit use of power tools unless in conjunction with local exhaust. Use hand tools whenever possible. Frequently clean the work area with HEPA filtered vacuum or wet sweeping to minimize the accumulation of debris. Do not use compressed air for clean-up.</p> <p>STORAGE: Store in original container in a dry area. Keep container closed when not in use.</p>																						
<p>EMPTY CONTAINERS: Product packaging may contain residue. Do not reuse.</p>																						
<p>EXPOSURE GUIDELINES</p> <table border="1" style="width: 100%;"> <thead> <tr> <th style="width: 30%;">MAJOR COMPONENT</th> <th style="width: 30%;">OSHA PEL</th> <th style="width: 40%;">MANUFACTURER'S REG.</th> </tr> </thead> <tbody> <tr> <td>Refractories, Fibers, Aluminosilicate</td> <td>None Established*</td> <td>0.5 fcc, 8-hr. TWA**</td> </tr> </tbody> </table> <p>OTHER OCCUPATIONAL EXPOSURE LEVELS (OEL)</p> <table border="1" style="width: 100%;"> <thead> <tr> <th style="width: 30%;">OTHER COMPONENTS</th> <th style="width: 30%;">OSHA PEL</th> <th style="width: 40%;">MANUFACTURER'S REG.</th> </tr> </thead> <tbody> <tr> <td>Silica, amorphous</td> <td>(80 mg/m³) * % SiO₂ • 7 or 20 mg/m³</td> <td>None Established</td> </tr> <tr> <td>Starch</td> <td>15 mg/m³ (total); 5 mg/m³ (respirable)</td> <td>None Established</td> </tr> </tbody> </table> <p>OTHER OCCUPATIONAL EXPOSURE LEVELS (OEL)</p> <table border="1" style="width: 100%;"> <thead> <tr> <th style="width: 30%;">OTHER COMPONENTS</th> <th style="width: 30%;">OSHA PEL</th> <th style="width: 40%;">MANUFACTURER'S REG.</th> </tr> </thead> <tbody> <tr> <td>% SiO₂ = Percent of crystalline silica</td> <td></td> <td></td> </tr> </tbody> </table>		MAJOR COMPONENT	OSHA PEL	MANUFACTURER'S REG.	Refractories, Fibers, Aluminosilicate	None Established*	0.5 fcc, 8-hr. TWA**	OTHER COMPONENTS	OSHA PEL	MANUFACTURER'S REG.	Silica, amorphous	(80 mg/m ³) * % SiO ₂ • 7 or 20 mg/m ³	None Established	Starch	15 mg/m ³ (total); 5 mg/m ³ (respirable)	None Established	OTHER COMPONENTS	OSHA PEL	MANUFACTURER'S REG.	% SiO ₂ = Percent of crystalline silica		
MAJOR COMPONENT	OSHA PEL	MANUFACTURER'S REG.																				
Refractories, Fibers, Aluminosilicate	None Established*	0.5 fcc, 8-hr. TWA**																				
OTHER COMPONENTS	OSHA PEL	MANUFACTURER'S REG.																				
Silica, amorphous	(80 mg/m ³) * % SiO ₂ • 7 or 20 mg/m ³	None Established																				
Starch	15 mg/m ³ (total); 5 mg/m ³ (respirable)	None Established																				
OTHER COMPONENTS	OSHA PEL	MANUFACTURER'S REG.																				
% SiO ₂ = Percent of crystalline silica																						
<p>ENGINEERING CONTROLS Use feasible engineering controls such as local exhaust ventilation, point of generation dust collection, down draft work stations, emission controlling tool designs, and materials handling equipment designed to minimize airborne fiber emissions.</p>																						
<p>PERSONAL PROTECTION EQUIPMENT</p> <p>Respiratory Protection – RCF: When engineering and/or administrative controls are insufficient to maintain workplace exposures within the 0.5 fcc REG, the use of appropriate respiratory protection, pursuant to the requirements of OSHA Standards 29 CFR 1910.134 and 29 CFR 1926.103, is recommended. The following information is provided as an example of appropriate respiratory protection for aluminosilicate fibers. The evaluation of workplace hazards and the identification of appropriate respiratory protection is best performed, on a case-by-case basis, by a qualified Industrial Hygienist.</p>																						

Chapter 12

MSDS No:	203	Date Prepared:	08/01/1987	Current Date:	4/13/2006 Last Revised: (04/13/2006)	MSDS No:	203	Date Prepared:	08/01/1987	Current Date:	4/13/2006 Last Revised: (04/13/2006)
MANUFACTURER'S RESPIRATORY PROTECTION RECOMMENDATIONS											
WHEN HANDLING RCF PRODUCTS											
Respirator Recommendation: ¹											
Not yet determined but expected to be below 5.0 fcc, based on operation "Relatively less than 0.6 fcc"											
Half-face, air-purifying respirator equipped with a NIOSH-certified P100 particulate filter cartridge.											
See recommendation below for individual worker requests.											
0.5 fcc - 5.0 fcc											
Full-facepiece, air-purifying respirator equipped with a NIOSH-certified P100 particulate filter cartridge or PAPR.											
5.0 fcc - 25 fcc											
Greater than 25 fcc											
When individual workers request respiratory protection as a matter of personal comfort or choice and exposures are relatively below 0.5 fcc (8-hr., TWA)											
A NIOSH-certified respirator, such as a disposable particulate respirator or respirators with filter cartridges rated N95 or better.											
¹ Note: The P100 recommendation is a conservative default choice; in some cases, solid arguments can be made that other respirator types (e.g., N95, R95, etc.) may be suitable for some tasks or work environments. The P100 recommendation is not designed to limit informed choices, provided that respiratory protection decisions comply with 29 CFR 1910.134.											
<u>Other Information:</u>											
• Concentrations based upon an eight-hour time weighted average (TWA) as determined by air samples collected and analyzed pursuant to NIOSH method 7400 (B) for airborne fibers.											
• The manufacturer recommends the use of a full-facepiece, air purifying respirator equipped with an appropriate particulate filter cartridge during furnace tear-out events and the removal of used RCF to control exposures to airborne fiber and the potential presence of crystalline silica. If exposure levels are known, the respiratory protection chart provided above may be applied.											
• Potential exposure to other airborne contaminants should be evaluated by a qualified Industrial Hygienist for the selection of appropriate respiratory protection and air monitoring.											
• In the absence of other objective data or when concentrations are unknown, the manufacturer recommends the use of a half-face, air-purifying respirator equipped with a NIOSH-certified P-100 particulate filter cartridge (See above note).											
• Wear gloves (e.g., cotton), head coverings and full body clothing as necessary to prevent skin irritation. Washable or disposable clothing may be used. If soiled work clothing home. If soiled work clothing must be taken home, employers should ensure employees are trained on the best practices to minimize or avoid non-work dust exposure (e.g., vacuum clothes before leaving the work area, wash work clothing separately, rinse washer before washing other household clothes, etc.).											
<u>Skin Protection:</u>											
Wear safety glasses with side shields or other forms of eye protection in compliance with appropriate OSHA standards to prevent eye irritation. The use of contact lenses is not recommended, unless used in conjunction with appropriate eye protection. Do not touch eyes with soiled body parts or materials. If possible, have eye-washing facilities readily available where eye irritation can occur.											
<u>Eye Protection:</u>											
Wear safety glasses with side shields or other forms of eye protection in compliance with appropriate OSHA standards to prevent eye irritation. The use of contact lenses is not recommended, unless used in conjunction with appropriate eye protection. Do not touch eyes with soiled body parts or materials. If possible, have eye-washing facilities readily available where eye irritation can occur.											
9. PHYSICAL AND CHEMICAL PROPERTIES											
ODOR AND APPEARANCE:											
CHEMICAL FAMILY:											
BOILING POINT:											
WATER SOLUBILITY (%):											
MELTING POINT:											
SPECIFIC GRAVITY:											
VAPOR PRESSURE:											
PH:											
VAPOR DENSITY (Air = 1):											
% VOLATILE:											
MOLECULAR FORMULA:											
10. STABILITY AND REACTIVITY											
CHEMICAL STABILITY:											
INCOMPATIBILITY:											
CONDITIONS TO AVOID:											
HAZARDOUS DECOMPOSITION PRODUCTS:											
Oxides of carbon and trace of ammonia may be released from starch during initial heating of this product.											
HAZARDOUS POLYMERIZATION:											
11. TOXICOLOGICAL INFORMATION											
HEALTH DATA SUMMARY:											
Epidemiological studies that include most people who have ever worked in domestic RCF production have indicated no increased incidence of respiratory disease or other significant health effects in occupationally exposed workers. In animal studies, long-term, high-dose inhalation exposure resulted in the development of respiratory disease in rats and hamsters.											
EPIDEMILOGY:											
The University of Cincinnati is conducting an ongoing epidemiologic investigation. The evidence obtained from employees in U. S. RCF manufacturing facilities is as follows:											
1) There is no evidence of any fibrotic lung disease (interstitial fibrosis) from evaluations of chest X-rays.											
2) There is no evidence of an elevated incidence of lung disease among RCF manufacturing employees.											
3) In early studies an apparent statistical "trend" within the exposed population was observed between RCF exposure duration and some measures of lung function. The observations were clinically insignificant. If these observations were made on an individual employee, the results would be interpreted as being within the normal (predicted) respiratory range. A more recent longitudinal study of employees with 5 or more pulmonary function tests refutes the earlier observations, finding no effect on lung function associated with RCF production experience. Initial data (circa 1987) seemed to indicate an interactive effect between smoking and RCF exposure; more recent data, however, found no interactive effect. Nevertheless, to promote good health, RCF employees are still actively encouraged not to smoke.											
4) Pleural plaques (thickening along the chest wall) have been observed in a small number of RCF employees. Some studies appear to show a relationship between the occurrence of pleural plaques on chest radiographs and the following variables: (a) years since RCF production hire date; (b) duration of RCF production employment; and (c) cumulative RCF exposure. The best evidence to date indicates that pleural plaques are a marker of exposure only. Pleural plaques are not associated with pulmonary impairment. The pathogenesis of pleural plaques remains incompletely understood; however, the mechanism appears to be an inflammatory response caused by inhaled fibers.											

Appendix - MSDS

MSDS No:	203	Date Prepared:	08/01/1987	Current Date:	4/13/2006	Date Prepared:	08/01/1987	Current Date:	4/13/2006
TOXICOLOGY:									
	A number of toxicological studies designed to identify any potential health effects from RCF exposure have been completed. In one study, conducted by the Research and Consulting Company, (Geneva, Switzerland), rats and hamsters were exposed to 30 mg/m ³ (about 200 fibers/c) of specially-prepared RCF for 6 hours/day, 5 days/week, for up to 24 months. In rats, a statistically significant increase in lung tumors was observed, two mesotheliomas (cancer of the pleural lining between the chest wall and lung) were also identified. Hamsters did not develop lung tumors; however, interstitial fibrosis and mesothelioma was found. Some, in the scientific community, have concluded that the "maximum tolerated dose" was exceeded and that significant particle contamination was a confounding issue; therefore, these study findings may not represent an accurate assessment of the potential for RCF to produce adverse health effects.								
In a related multi-dose study with a similar protocol, other rats were exposed to doses of 16 mg/m ³ , 9 mg/m ³ , 3 mg/m ³ which corresponds to about 115, 75, and 25 fibers per cubic centimeter respectively. This study found no statistically significant increase in lung cancer. Some cases of pleural and parenchymal fibrosis were seen in the 16 mg/m ³ dose group. Some cases of mild fibrosis and one mesothelioma were observed in the 9 mg/m ³ group. No acute respiratory effects were seen in the rats in the 3 mg/m ³ exposure group, which suggests that there may be a dose/response threshold, below which irreversible respiratory impacts do not occur.									
	Other toxicological studies have been conducted which utilized non-physiological exposure methods such as intrapleural, intraperitoneal and intratracheal implantation or injection. Some of these studies have found that RCF is a potential carcinogen. Some experts, however, suggest that these tests have limited relevance because they bypass many of the biological mechanisms that prevent fiber deposition or facilitate fiber clearance.								
	Silica/amorphous: Toxic effects described in animals from single inhalation exposures of amorphous silica include upper respiratory irritation, lung congestion, bronchitis, and emphysema. Repeated inhalation exposures at a concentration of 50 or 150 mg/m ³ produced increased lung weights and lung changes. No progressive pulmonary fibrosis was seen and the observed lung changes were reversible. No adverse effects were observed in this study at 10 mg/m ³ . No animal test reports are available to define the carcinogenic, mutagenic, or reproductive effects.								
	To obtain more epidemiology or toxicology information, please call the toll free telephone number for the Thermal Ceramics Product Stewardship Program found in Section 16 - Other Information.								
12. ECOLOGICAL INFORMATION									
	No ecological concerns have been identified.								
13. DISPOSAL CONSIDERATIONS									
	WASTE MANAGEMENT: To prevent waste materials from becoming airborne during waste storage, transportation and disposal, a covered container or plastic bagging is recommended.								
DISPOSAL:									
	RCF, as manufactured, is not classified as a hazardous waste according to Federal regulations (40 CFR 261). As manufactured, RCF was tested using EPA's Toxic Characteristic Leaching Procedure (TCLP). Results showed there were no detectable contaminants or detectable leachable contaminants that exceeded the regulatory levels. Any processing, use, alteration or chemical additions to the product, as purchased, may alter the disposal requirements. Under Federal regulations, if it is the waste generator's responsibility to properly characterize a waste material, to determine if it is a "hazardous" waste. Check local, regional, state or provincial regulations to identify all applicable disposal requirements.								
14. TRANSPORT INFORMATION									
U.S. DEPARTMENT OF TRANSPORTATION (DOT)									
Hazard Class:	Not Regulated	United Nations (UN) Number:	Not Applicable	Labels:	Not Applicable	North America (NA) Number:	Not Applicable	Placards:	Product Name

Chapter 12

MSDS No: 203 **Date Prepared:** 08/01/1987 **Current Date:** 4/13/2006
Last Revised: (4/13/2006)

IARC and NTP did not evaluate after-service RCF, which may contain various crystalline phases. However, an analysis of after-service RCF samples obtained pursuant to an exposure monitoring agreement between the EPA, found that in the furnace conditions sampled, most did not contain detectable levels of crystalline silica. Other relevant RCF studies found that (1) simulated after-service RCF showed little, or no, activity where exposure was by inhalation or by intraperitoneal injection; and (2) after-service RCF was not cytotoxic to macrophage-like cells at concentrations up to 320 $\mu\text{g}/\text{cm}^3$ - by comparison, pure quartz or cristobalite were significantly active at much lower levels (circa 20 $\mu\text{g}/\text{cm}^3$).
RGE AFTER-SERVICE REMOVAL:
 Respiratory protection should be provided in compliance with the Product Stewardship Program and OSHA standards. During removal operations, a FULL FACE RESPIRATOR is recommended to reduce inhalation exposure along with eye and respiratory tract irritation. A specific evaluation of workplace hazards and the identification of appropriate respiratory protection is best performed, on a case-by-case basis, by a qualified industrial hygiene professional.
For more information, call the Thermal Ceramics Product Stewardship Hotline (800-722-5681).

PRODUCT STEWARDSHIP PROGRAM:

Morgan Thermal Ceramics has established a program to provide customers with up-to-date information regarding the proper use and handling of RCF. In addition, Thermal Ceramics has established a program to monitor airborne fiber concentrations at customer facilities. If you would like more information about this program, please call your local supplier or visit one of the following web sites.

Thermal Ceramics - Global
 Refractory Ceramic Fibers Coalition (USA)
 ECFIA (Europe)

www.thermalceramics.com
www.RCFC.net
www.ecfia.org

LABELING:

As product information labels may be required on RCF packages, check local destination regulations before shipping

MSDS No:	203	Date Prepared:	08/01/1987	Current Date:	4/13/2006
<small>Last Revised: (4/13/2006)</small>					

American Conference of Governmental Industrial Hygienists

Carriage of Dangerous Goods by Road (International Regulation)

Clean Air Act

Chemical Abusers Service

Comprehensive Environmental Response, Compensation and Liability Act

Domestic Substances List

Environmental Protection Agency

EU:

EU:

fib.:

HEPA:

HMS:

IARC:

IATA:

IMDG:

mg/m³:

mpcf:

NFPA:

NIOSH:

OSHA:

29 CFR 1910.134 & 1928.103:

29 CFR 1910.1200 & 1928.59:

PEL:

PN:

PNOC:

PNP:

PSP:

RCFC:

RCRA:

REG:

REL:

RID:

SARA:

SARA Title III:

SARA Section 302:

SARA Section 304:

SARA Section 311:

SARA Section 312:

SARA Section 313:

STEL:

SVF:

TG1:

TLV:

TSCA:

TWA:

WHMIS:

Workplace Hazardous Materials Information System (Canada)

Revision Summary:

Section 1: The following products have been added:

Thermoelect® HT, HP, LD, A, AR, Cer-Wool® Wet Wrap, Wet Wrap HT.

MSDS Prepared By:

THE THERMAL CERAMICS ENVIRONMENTAL, HEALTH & SAFETY DEPARTMENT

DISCLAIMER

The information presented herein is presented in good faith and believed to be accurate as of the effective date of this Material Safety Data Sheet. Employers may use this MSDS to supplement other information gathered by them in their efforts to assure the health and safety of their employees and the proper use of the product. This summary of the relevant data reflects professional judgment; employers should note that information perceived to be less relevant has not been included in this MSDS. Therefore, given the summary nature of this document, Thermal Ceramics does not extend any warranty (expressed or implied), assume any responsibility, or make any representation regarding the completeness of this information or its suitability for the purposes envisioned by the user.


DEFINITIONS:

Appendix - MSDS

12.6 MSDS 0732 RTV Silicone 732

Polymerization	Will not Occur	X					
Section VI—Health Hazard Data							
Route(s) of Entry:							
Health Hazards (Acute and Chronic)	Inhalation?	Yes	Skin?	Yes	Ingestion?	Yes	Inhalation?
Health Hazards (Acute and Chronic)	EYES: Direct contact may burn eyes, irritate severely or permanently injure eye depending on exposure. SKIN: May cause irritation. INHALATION: May cause drowsiness & irritate nose and throat. Vapors may injure blood, lungs, liver and nervous system. INGESTION: Small amounts should not injure. Inhalation liquid while vomiting can injure lungs seriously.						
Carcinogenicity:	N/A	NTP?	IARC Monographs?	IARC Monographs?	OSHA Regulated		
Signs and Symptoms of Exposure:							
Medical Conditions Generally aggravated by Exposure	Vary according to degree of exposure. Minimal exposure should not injure. See above for symptoms of prolonged exposure.						
Emergency and First Aid Procedures	Prolonged toluene overexposure may aggravate existing eye, skin & respiratory disorder.						
	EYES: Flush with water for 15 minutes, get medical attention. SKIN: Wash with soap and water. INHALATION: Remove to fresh air. INGESTION: Get immediate medical attention if a large amount is swallowed..						
Section VII—Precautions for Safe Handling and Use							
Steps to be Taken in Case Material is Released or Spilled	Use absorbent material to collect and contain for salvage or disposal. Remove all source of ignition and wear proper protection equipment.						
Waste Disposal Method	Dispose in accordance with State, Federal, and local anti-pollution and waste disposal regulations.						
Precautions to be Taken in Handling and Storing	Keep container closed and away from heat, sparks and open flame.						
Other Precautions	Static electricity may accumulate and create fire hazard. Ground fixed equipment.						
Section VIII—Control Measures							
Respiratory Protection (Specify Type)	Organic vapor type.						
Ventilation:	Local Exhaust	Recommended	Special	N/A			
Protective Gloves	Rubber or plastic	Recommended (General)	Other	N/A			
Other Protective Clothing or Equipment	Eye Protection			Chemical worker goggles			
Work/Hygiene Practices	Aprons, boots						
	Wash promptly upon any detectable contact.						
The information on this data sheet represents our current data and best opinion as to the proper use in handling of this product under normal conditions. Any use of the product which is not in conformance with this data sheet or which involves using the product in combination with any other product or any other process is the responsibility of the user.							
Extincting Media	Water, water fog, Carbon Dioxide, dry chemical, foam.						
Special Fire Fighting Procedures	Self contained breathing apparatus and protective clothing should be worn in fighting fires involving chemicals.						
Unusual Fire and Explosion Hazards	Name Known.						
Section V—Reactivity Data							
Stability	Unstable	Conditions to Avoid					
	Stable	X	Exposure to air until ready to use.				
Incompatibility (Materials to Avoid)	Oxidizing material can cause a reaction.						
Hazardous Decomposition or Byproducts	Silicon Dioxide, Carbon Dioxide and traces of incompletely burned carbon products.						
Hazardous	May Occur	Conditions to Avoid	N/A				

12.1 MSDS MagnaForm Boards



ESTERN INDUSTRIAL CERAMICS

MagnaForm

MATERIAL SAFETY DATA SHEET

MANUFACTURER/SUPPLIER: WESTERN INDUSTRIAL CERAMICS, INC.
ADDRESS: 10725 S.W. TUALATIN - SHERWOOD RD., TUALATIN, OREGON 97062
EMERGENCY PHONE: 1 - 800 - 727 - 9424
1 - 503 - 692 - 3770

SECTION I: PRODUCT IDENTIFICATION:

TRADE NAME:
MAGNAFORM BOARDS & SHAPES

CAS NUMBER:	MIXTURE
SYNONYM(S):	CERAMIC FIBER, REFRACTORY FIBER; REFRACTORY CERAMIC FIBER; MMVF; R.C.F.
CHEMICAL FAMILY;	VITREOUS ALUMINOSILICATE FIBERS
MOLECULAR FORMULA:	NA
MOLECULAR WEIGHT:	NA
PRODUCT CODE:	NA
	HIERARCHY: NA
COMMENTS:	MAGNAFORM BOARDS & SHAPES are made of bulk refractory fiber from several manufacturers, inorganic binders, and additionally, in some compositions from starches, mineral wool, or polycrystalline alumina fiber

SECTION II: PRODUCT HAZARD SUMMARY:

HEALTH:	WARNING! POSSIBLE CANCER HAZARD BY INHALATION MAY BE HARMFUL IF INHALED (hazard depends on duration and level of exposure) MAY BE IRRITATING TO SKIN, EYES, AND RESPIRATORY TRACT
FLAMMABILITY:	NON-COMBUSTIBLE
REACTIVITY:	STABLE

ND = NO DATA
NA = NOT APPLICABLE